



A Remote Operation Panel for even greater operability during shooting, equipped with a new touch panel

AK-HRP1010

The AK-HRP1010GJ is the successor model of the AK-HRP1000 ROP, supporting studio camera systems, remote camera and Varicam series in the future.

Key Features

1/4 rack size, four units can be installed in a single 19-inch EIA rack.

High-resolution 3.5-inch color LCD touch panel and easy-to-use operation button layout.

IP connection supported, enabling control of studio cameras and Panasonic's PTZ cameras*.

User-assignable knobs and priority buttons enable rapid operation of frequently-used functions.

Up to 99 cameras can be switched between and controlled with a single unit.



AK-HRP1010

<https://eu.connect.panasonic.com/ae/en/broadcast-proav/ak-hrp1010>

General -> Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
General -> Power Consumption	0.9 A (Power supply from camera/CCU: 10 V - 16 V DC) 0.3 A (PoE power supply)
General -> Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Operating Humidity	90% or less
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 1.7 kg (3.75 lb)
General -> Dimensions	W 102 mm x H 385 mm x D 113 mm (4 inches x 15-3/16 inches x 4-7/16 inches)
General -> Camera/CCU Control	Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected) *1, 12 V DC (when camera connected) *1
General -> Maximum Cable Length	When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft)
Monitor -> LCD monitor	LCD color monitor, touch panel support
Input/Output -> CCU connector	10-pin, male x 1
Input/Output -> PREVIEW connector	9-pin, female x 1
Input/Output -> LAN connector	RJ-45 x 1
Footnote Description	Can be provided from CCU.