



Indoor pan-tilt head

AW-PH360

Cost effective pan tilt head

Key Features

Pan angle: 300°, Tilt angle: 190°

Smooth starts and stops with soft landing function

Maximum load: 4kg

AW-PH360

<https://eu.connect.panasonic.com/ae/en/products/broadcast-proav/aw-ph360>

Power Supply/Power Consumption	DC12 V / 1.3 A (pan-tilt head only)
Weight	Approx. 3.5 kg (Approx. 7.7 lb)
Dimensions (W x H x D) (Pan-Tilt Head only, Excluding Protrusions)	146 mm x 245 mm x 161.5 mm (5-3/4 inches x 9-5/8 inches x 6-3/8 inches)
Maximum Load (Including with a Camera, a Lens and a Teleprompter)	Approx. 4 kg (Approx. 8.8 lb)
Pan/Tilt Angle (Maximum Pan/Tilt Speed)	Pan Approx. $\pm 150^\circ$ (30°/s) Tilt Approx. $\pm 95^\circ$ (25°/s)
Stop Accuracy	under ± 3 arcminutes (0.05°)
Quietness	under NC30
Maximum Control Distance (when using AW-RP120G/AW-RP50)	1000 m
Interface RS232C	Control cable: Local procurement
Maximum Preset Memories	50
Applicable Lens	MD lenses
Tally Light	Standard equipment (non-removable)
Teleprompter Output	-
Accessory	DC cable (Approx. 3 m), Camera cable (Approx. 0.6 m)
AC Adaptor/Power Cable	AC adaptor AW-PS550/551*(optional) * Not available in some areas.