



**49" LCD IPS Panel, 700 cd/m2, 24/7 operation,  
DIGITAL LINK, portrait mode**

## **TH-49LF80**

High brightness LED backlight flat panel offering high reliability and operability ideal for rental & staging and signage applications

### **Key Features**

49", 700 cd/m2, 6.3 mm bezel width

High brightness and strong reliability enable continuous 24/7 operation with highly durable panel

System Expandability - The DIGITAL LINK function, based on HDBaseT™ technology, enables simple setup and low system costs

Durable failover and fallback function with simplified workflow solution





## TH-49LF80

<https://eu.connect.panasonic.com/sk/en/products/professional-displays/th-49lf80>

<b>Screen Size</b>	49-inch (1232 mm)
<b>Panel Type</b>	LCD IPS Panel/E-LED
<b>Aspect Ratio</b>	16:9
<b>Effective Display Area (W x H)</b>	1073 x 604 mm (42.2" x 23.8")
<b>Number of Pixels (H x V)</b>	1920 x 1080 pixels
<b>Brightness</b>	700 cd/m2
<b>Contrast Ratio</b>	1300:1
<b>Dynamic Contrast</b>	50000:1
<b>Response Time</b>	8 ms (GtoG)
<b>Viewing Angle (Horizontal/Vertical)</b>	178°/178°(CR≥10)
<b>Power Requirements</b>	110-127/220-240 V AC,50/60 Hz
<b>Power Consumption</b>	175W
<b>Power Off Condition</b>	Approx.0.3W
<b>Standby Condition</b>	Approx.0.5W
<b>Dimensions (W x H x D)</b>	1093 x 623 x 72 mm(43.1" x 24.6" x 2.8")
<b>Dimensions (W x H x D) Excluding Handle Part</b>	1093 x 623 x 57 mm(43.1" x 24.6" x 2.3")
<b>Bezel Width</b>	T/R/L/B : 6.3 mm (0.25")
<b>Weight</b>	19.0 kg(41.9 lbs.)
<b>Wall-Hanging Pitch</b>	VESA Compliant 400 x 400 mm(15.8" x 15.8")
<b>Operating Environment</b>	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
<b>Panel Surface Treatment</b>	Anti-Glare
<b>Haze</b>	10%