



LCD, 3300 lumens, XGA, 28dB quiet operation, long lamp replacement cycle

PT-LB353

Designed for education and corporate applications

Key Features

LCD, 3300 lumens, XGA

Lamp and filter replacement cycle of up to 10,000 hours
(Reduces TCO)

Quiet 28 dB Operation for Distraction - free Viewing

16,000:1 contrast ratio



PT-LB353

<https://eu.connect.panasonic.com/b/en/products/projectors/pt-lb353>

Power Supply	AC100-240V 3.5A 50/60 Hz
Power Consumption	300W 6W when Standby mode set to Normal, 0.5W when Standby mode set to Eco*1
LCD Panel Panel Size	16.0 mm (0.63 inches) diagonal (4:3 aspect ratio)
LCD Panel Display Method	Transparent LCD panel (x 3, R/G/B)
LCD Panel Drive Method	Active matrix method
LCD Panel Pixels	786,432 (1,024 x 768) x 3, total of 2,359,296 pixels
LCD Panel Pixel Configuration	Stripe
Lens	Manual zoom (1.2x), manual focus F 1.6- 1.76, f 19.16- 23.02 mm
Throw Ratio	1.48- 1.78:1
Lamp	230 W UHM lamp
Lamp/Filter*2 Replacement Cycle	Normal: 5,000hrs / Eco1: 6,000hrs / Eco2: 10,000hrs
Screen Size	30-300 inches (0.76 -7.62 m) diagonally, 4:3 aspect ratio
Colors	Full color (16,777,216 colors)
Brightness*3	3,300 lumens (lamp power: normal)
Center-to-Corner Uniformity*3	80%
Contrast*3	16,000:1 (all white/all black, Image mode:Dynamic, Lamp control: Normal, Iris: On)
Resolution	1,024 x 768 pixels (Input signals that exceed this resolution will be converted to 1,024 x 768 pixels.)
Optical Axis Shift	6:1 (fixed)
Keystone Correction Range	Vertical: ±30°, horizontal: ±15°
Installation	Ceiling/floor, front/rear (menu selection)
Built-in Speaker Output Power	10 W (monaural) x 1
Terminals HDMI In	HDMI 19-pin x 1, HDCP and Deep Color compatible Audio signal: linear PCM (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
Terminals Computer (RGB) 1 In	D-sub HD 15-pin (female) x 1
Terminals Computer (RGB) 1 In R, G, B	R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: high impedance, TTL (positive/negative automatic)
Terminals Computer (RGB) 1 In Y, PB (CB), PR (CR)	Y: 1.0 Vp-p (including sync signal), 75 ohms PB (CB), PR (CR): 0.7 Vp-p, 75 ohms
Terminals Computer (RGB) 1 In S-Video	Y: 1.0 Vp-p; C: 0.286 Vp-p, 75 ohms NOTE: D-Sub -S video conversion cable (ET-ADSV) is required.
Terminals Computer (RGB) 2 In	D-sub HD 15-pin (female) x 1
Terminals Computer (RGB) 2 In R, G, B	R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: TTL (positive/negative automatic)
Terminals Monitor Out	D-sub HD 15-pin (female) x 1
Terminals Monitor Out R, G, B	R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: TTL (positive/negative polarity compatible)
Terminals Video In	Pin jack x 1, 1.0 Vp-p, 75 ohms
Terminals Audio In 1	M3 (L, R) x 1, 0.5 Vrms
Terminals Audio In 2	Pin jack x 2 (L, R x 1), 0.5 Vrms
Terminals Audio Out	M3 (L, R) x 1 (monitor out: 0- 2.0 Vrms, variable)
Terminals Serial In	D-sub 9-pin (female) x 1, for external control (RS-232C compliant)
Terminals LAN	RJ-45 x 1, for network connection, compliant with PLink™, 100Base-TX/10Base-T
Terminals USB	USB A (type A) connector x 1, for Memory Viewer/Wireless Module (Out put 5V MAX 500mA) USB B (type B) connector x 1, for USB Display
Power Cord Length	1.8 m (5 ft 11 in)
Cabinet Materials	Molded plastic
Dimensions (W x H x D)	335 x 96* 4 x 252 mm (13-3/16 x 3-25/32*4 x 9-29/32 inches)
Weight*5	Approx. 2.9 kg (6.4 lbs)
Operation Noise*3	37 dB (Lamp power: Normal), 33 dB (Lamp power: Eco1) 28 dB (Lamp power: Eco2)

Operating Temperature	5°C-40°C (41°F-104°F)
	[at less than 1,400 m (4,593 ft.);[High land]:[off]
	5°C-35°C (41°F-95°F)
	[at 1,400 m to 2,700 m (4,593 ft. to 8,858 ft.);[High land]:[on 1]
Operating Humidity	5°C-30°C (41°F-86°F)
	[at 2,700 m to 3,000 m (8,858 ft. to 9,843 ft.);[High land]:[on 2]
Note	20%-80% (no condensation)
	*1 When the Standby mode is set to Eco, network functions such as power on over the LAN network will not operate. Also, only certain commands can be received for external control using the serial terminal.
	*2 Usage environment affects the duration of filter.
	*3 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.
	*4 With legs at shortest position.
	*5 Average value. May differ depending on models.
	*6 Operation range differs depending on environments.
Technology	LCD
Brightness	3300 lumens