



1/4-type rackformaat ondersteunt PoE+- en IP-bediening

AK-HRP1000

1/4-type rackformaat extern bedieningspaneel dat PoE+- en IP-bediening ondersteunt

Key Features

Kleuren-LCD-afleescherm voor GUI-bediening, en ondersteunt daarnaast PoE+- en IP-bediening

Variabele mastergain, kleurtemperatuur en masterflare kunnen worden toegewezen aan een gebruikersknop

Joystick-bedieningshendel voor iris-/voetstukbediening

Kan worden gebruikt met een mix van studio- en Panasonic externe camera's via IP-verbindingen



AK-HRP1000

<https://eu.connect.panasonic.com/be/nl/broadcast-proav/accessories/ak-hrp1000>

General -> Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
General -> Power Consumption	0.51 A (Power supply from camera: 10 V - 16 V DC) 0.15 A (PoE power supply)
General -> Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Operating Humidity	90 % or less
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 1.7 kg (3.75 lb)
General -> Dimensions	W 102 mm x H 385 mm x D 113 mm (4 inches x 15-3/16 inches x 4-7/16 inches)
General -> Camera/CCU Control	Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected) ^{*1} , 12 V DC (when camera connected) ^{*1}
General -> Maximum Cable Length	When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft)
Footnote Description	Can be provided from CCU.