



Built for continuous 24/7 operation. Perfect for interactive digital signage in public places thanks to the ShadowSense multi-touch technology. 55", LCD IPS Panel, 700 cd/m², ShadowSense multi-touch display.

TH-55LF80-SST

High brightness, robust and accurate touch display. Built for continuous 24/7 operation. Perfect for interactive digital signage in public places thanks to the ShadowSense multi-touch technology.

Key Features

55", 700cd/m², 24/7 Operation

10-point multi-touch interactive display using ShadowSense(TM) technology

The touch technology is immune to the ambient light and works even in bright environments.

Made with 4mm hardened safety glass, the touchscreens are durable and very tolerant of dirt and objects blocking the sensors

DIGITAL LINK connectivity



Media
Player





TH-55LF80-SST

<https://eu.connect.panasonic.com/ch/en/products/professional-displays/th-55lf80-sst>

Screen Size	55-inch (1387 mm)
Panel Type	LCD IPS Panel/E-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1209 x 680 mm (47.6" x 26.7")
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	700 cd/m2
Contrast Ratio	1300:1
Dynamic Contrast	50000:1
Response Time	8 ms (GtoG)
Viewing Angle (Horizontal/Vertical)	178°/178°(CR≥10)
Power Requirements	110-127/220-240 V AC,50/60 Hz
Power Consumption	190W
Power Off Condition	Approx.0.3W
Standby Condition	Approx.0.5W
Dimensions (W x H x D)	1229 x 699 x 72 mm(48.4" x 27.6" x 2.8")
Dimensions (W x H x D) Excluding Handle Part	1229 x 699 x 57 mm(48.4" x 27.6" x 2.3")
Bezel Width	T/R/L/B : 6.3 mm (0.25")
Weight	24.7kg (54.5 lbs.)
Wall-Hanging Pitch	VESA Compliant 400 x 400 mm(15.8" x 15.8")
Operating Environment	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
Panel Surface Treatment	Anti-Glare
Haze	10%