



Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 86", 400 cd/m², stylish design display with narrow bezel and IPS panel for clear off-axis visibility.

TH-86CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

Key Features

86", 400 cd/m²

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

IPS Panel for superb viewing experience from any angle

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





TH-86CQ1

<https://eu.connect.panasonic.com/ch/en/products/professional-displays/th-86cq1>

Screen size (diagonal) (inch)	86-inch
Screen size (diagonal) (mm)	2177.4 mm
Aspect Ratio	16:9
Panel Type	IPS Panel / Edge LED
Effective display area (W x H) (mm)	1897 x 1068 mm
Effective display area (W x H) (inch)	74.70 x 42.00 inch
Resolution	3840 x 2160
Brightness (typ.)	400 cd/m2
Contrast Ratio	1200 : 1
Response Time	8 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR>10)
Terminals HDMI In	HDMI TYPE-A Connector x 2
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1
Terminals Serial	D-sub 9-pin x 1 (Input, RS-232C Compatible)
Terminals Audio Out	RCA Terminal (L / R) x 1
Terminals LAN	RJ45 x 1, 10BASE-T/100BASE-TX
Terminals USB	USB Type A Connector x 1, DC 5 V/0.5 A (USB 2.0 is supported)
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	AC 110 - 127 V 50 Hz / 60 Hz
Power Consumption	340 W
Power Off Condition	Approx. 0.5 W
Standby Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1929 x 1103 x 80 mm
Dimensions (W x H x D) (inch)	76.0" x 43.5" x 3.2"
Bezel width (mm)	(T/B/L/R) 15.3 mm
Bezel width (inch)	T/B/L/R 0.61"
Weight (kg)	Approx. 50 kg
Weight (lbs.)	Approx. 110.3 lbs
Wall-hanging pitch (mm)	VESA Compliant 600 x 400 mm
Wall-hanging pitch (inch)	VESA Compliant 23.6" x 15.7"
Operating Time	16 h/day
Operating Environment	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation)