



La gamme SQE1 dotée d'une résolution 4K prend en charge une installation en mode portrait et offre un fonctionnement 24 h/24 et 7 j/7 avec une luminosité de 500 cd/m2 et une connectivité haut de gamme. Une solution idéale pour une installation dans les li

TH-43SQE1

Une résolution quatre fois supérieure au Full HD pour un contenu vidéo 4K/60p avec des images très détaillées. Compatible avec une vaste gamme d'applications et un design qui se fond dans le décor.

Key Features

43", 500 cd/m2, écran 4K à la conception fine et élégante et fonctionnement 24 h/24 et 7 j/7


Lecteur média USB 4K : élimine le recours à des appareils externes et permet d'effectuer des mises à jour via LAN

Port Intel® SDM (Smart Display Module). 4 ports HDMI, port USB de types A et C, connecteurs DP (entrée/sortie), fonction HDMI-CEC prise en charge

Embedded Wi-Fi and HTML5 browser

Installation aisée et flexible en mode portrait ou paysage





TH-43SQE1

<https://eu.connect.panasonic.com/ch/fr/eccrans-professionnels/th-43sqe1>

DISPLAY PANEL -> Screen Size	43-inch class (42.5-inch / 1079.8 mm)
DISPLAY PANEL -> Brightness (typ.)	500 cd/m ²
DISPLAY PANEL -> Aspect ratio	16:9
DISPLAY PANEL -> Effective Display Area (W x H)	941.1 x 529.4 mm (37.05" x 20.84")
DISPLAY PANEL -> Resolution	3840 x 2160
DISPLAY PANEL -> Contrast Ratio (typ.)	1200:1
DISPLAY PANEL -> Dynamic Contrast Ratio	50000:1
DISPLAY PANEL -> Response Time (typ.)	8.0 ms (G to G)
DISPLAY PANEL -> Viewing Angle(H / V)	178° / 178° (CR>10)
DISPLAY PANEL -> Panel Surface Treatment	Anti-glare type
DISPLAY PANEL -> Haze	0.01
CONNECTION TERMINAL -> HDMI IN	HDMI™ Type A Connector x 4 (HDCP 2.2)
CONNECTION TERMINAL -> DisplayPort IN	DisplayPort x 1 (HDCP 1.3)
CONNECTION TERMINAL -> DisplayPort OUT	DisplayPort x 1 (HDCP 1.3)
CONNECTION TERMINAL -> PC IN	Mini D-Sub 15-pin (DDC2B) x 1 RGB: 0.7 Vp-p (75 Ω) HD/VD: TTL (High impedance)
CONNECTION TERMINAL -> SERIAL IN	D-sub 9-pin (Female) x 1, RS-232C Compatible
CONNECTION TERMINAL -> IR IN	Stereo mini jack (M3) x 1
CONNECTION TERMINAL -> AUDIO IN (L / R)	Pin jack (L / R) x 1
CONNECTION TERMINAL -> AUDIO OUT (L / R)	Stereo mini jack (M3) x 1
CONNECTION TERMINAL -> DIGITAL AUDIO OUT	SPDIF x 1
CONNECTION TERMINAL -> LAN	RJ45 x 1 Compatible with PLink™ RJ45 10BASE-T/100BASE-TX
CONNECTION TERMINAL -> USB TYPE A	USB connector Type A (5 V/0.5 A) x 2, (Internal) Type A x 1
CONNECTION TERMINAL -> USB TYPE C	USB connector Type C (5 V/1.5 A) x 1
CONNECTION TERMINAL -> SLOT	Intel® SDM specification (SDM-S / SDM-L, Supply power 12 V / Max 3.5 A)
CONNECTION TERMINAL -> Wi-Fi	Built-in, IEEE 802.11. a/b/g/n/ Dual Wi-Fi CERTIFIED
AUDIO -> Built in Speaker	16 W [8 W + 8 W]
ELECTRICAL -> Power Supply	AC 110 - 240 V 50 Hz / 60 Hz
ELECTRICAL -> Power Consumption	172 W (SLOT not in use: 119 W)
ELECTRICAL -> On Mode Average Power Consumption *1	96 W
ELECTRICAL -> Power Off Condition	0 W
ELECTRICAL -> Stand-by Condition	Approx. 0.5 W
ELECTRICAL -> Apparent power	173 W (SLOT not in use:128 W) (AC 110-127 V)172 W (SLOT not in use:121 W) (AC 220-240 V)
ELECTRICAL -> Energy efficiency class for Europe	G class
MECHANICAL -> Dimension(W)	966 mm (38.01")
MECHANICAL -> Dimension(H)	576 mm (22.68"), 558 mm (21.94")
MECHANICAL -> Dimension(D)	106 mm (4.17")
MECHANICAL -> Weight	Approx. 10.3 kg (22.7 lbs)
MECHANICAL -> Bezel Width(T)	9.6 mm (0.38")
MECHANICAL -> Bezel Width(B)	13.2 mm (0.52")
MECHANICAL -> Bezel Width(L)	9.6 mm (0.38")
MECHANICAL -> Bezel Width(R)	9.6 mm (0.38")
MECHANICAL -> Pitch for Wall-Hanging / Screw / Screw hole depth	VESA Compliant 200 x 200 mm (7.9" x 7.9") / M6 / 10 mm (0.39"), Allowable screw length 23 mm (0.91")
INSTALLATION -> Orientation	Landscape / Portrait
INSTALLATION -> Tilting Angle	Landscape : 20 degrees forward Portrait : 20 degrees forward
INSTALLATION -> Operating Time *2	24h / day
ENVIRONMENT -> Operating Environment(Temperature)	0°C to 40°C (32°F to 104°F) : 0°C to 35°C (32°F to 95°F)

ENVIRONMENTAL -> Operating 20% to 80%
Environment(Humidity) (No
condensation)

Note de bas de page

1. : When installing the display vertically, be sure that the power indicator comes to the right side.
2. : Excluding remote controller sensor box
3. : Including remote controller sensor box
4. : Please contact your sales representative with regard to the tilt angle before installation.
5. : In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.