



4K Memory Card Camera Recorder

AG-UX180

4K/UHD/FHD Camcorder with 24mm industry-best wide-angle*, 20x optical zoom and super-slow motion recording

Key Features

20x optical zoom and 24mm industry-best wide-angle* LEICA DICOMAR lens

1.0-type 4K MOS Sensor with 4K 24p and UHD 60p/50p recording capabilities

Intelligent Auto-Focus supports smooth and fast focusing when shooting in 4K

High-Resolution Intelligent Zoom increases zooming capability by 30x whilst maintaining high resolution

Super-Slow Motion recording at 120fps in FHD





AG-UX180

<https://eu.connect.panasonic.com/cz/en/products/broadcast-proav/ag-ux180>

General

Power	DC 7.28 V (when the battery is used) DC 12 V (when the AC adaptor is used)
Power Consumption	19.7 W (when the LCD monitor is used)
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10 % to 80 % (no condensation)
Weight	Body: Approx. 2.0 kg (4.41 lb) (body only, excluding lens hood, battery, and accessories) Shooting: Approx. 2.4 kg (5.29 lb) (including lens hood, battery, and eye cup)
Dimensions	173 mm (W) x 195 mm (H) x 346 mm (D) (6-13/16 inches x 7-11/16 inches x 13-5/8 inches) (excluding protrusion and eye cup) 173 mm (W) x 195 mm (H) x 392 mm (D) (6-13/16 inches x 7-11/16 inches x 15-7/16 inches) (including eye cup, excluding protrusion)
Camera Unit	
Pickup Devices	1.0-type (effective size) MOS solid state image sensor
Effective Pixels	8.79 megapixel: UHD/FHD 59.94p/29.97p/23.98p 9.46 megapixel: 4K 24p
Lens	Optical image stabilizer lens, optical 20x motorized zoom F2.8 to F4.5 (f=8.8 mm to 176 mm) 35 mm equivalent: f=25.4 mm to 508.0 mm: UHD/FHD 59.94p/29.97p/23.98p f=24.0 mm to 480.0 mm: 4K24.00p Filter Diameter: 67 mm ND Filter: 4 Positions (OFF, 1/4, 1/16, 1/64) IR Filter: Incorporates the ON/OFF control function Shortest Shooting Distance (M.O.D.): Approx. 1.0 m from the front lens
Gain Setting	L/M/H selector switch Standard mode: 0 dB to 24 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H) Extended ON: -3 dB to 24 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H) 30 dB and 36 dB switched (when assigning [S. GAIN] to the USER button)
Color Temperature Setting	ATW, ATW LOCK, Ach, Bch, preset 3200 K/preset 5600 K/VAR (2000 K to 15000 K)

Shutter Speed	<p>When [SYSTEM MODE] = 59.94 Hz</p> <p>60i/60p mode: 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.</p> <p>30p mode: 1/30 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.</p> <p>24p mode: 1/24 sec., 1/48 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.</p> <p>When [SYSTEM MODE] = 50.00 Hz</p> <p>50i/50p mode: 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.</p> <p>25p mode: 1/25 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.</p>
Shutter Speed (Slow Shutter)	<p>When [SYSTEM MODE] = 59.94 Hz</p> <p>60i/60p mode: 1/2 sec., 1/4 sec., 1/8 sec., 1/15 sec., 1/30 sec., 30p mode: 1/2 sec., 1/4 sec., 1/8 sec., 1/15 sec.</p> <p>24p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec.</p> <p>When [SYSTEM MODE] = 50.00 Hz</p> <p>50i/50p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec., 1/25 sec.</p> <p>25p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec.</p>
Shutter Speed (Synchro Scan)	<p>When [SYSTEM MODE] = 59.94 Hz</p> <p>59.94i/59.94p mode: 1/60.0 sec. to 1/249.7 sec.</p> <p>29.97p mode: 1/30.0 sec. to 1/249.7 sec.</p> <p>23.98p mode: 1/24.0 sec. to 1/249.6 sec.</p> <p>24.00p mode: 1/24.0 sec. to 1/249.9 sec.</p> <p>When [SYSTEM MODE] = 50.00 Hz</p> <p>50i/50p mode: 1/50.0 sec. to 1/250.0 sec.</p> <p>25p mode: 1/25.0 sec. to 1/250.0 sec.</p>
VFR Recording Frame Rate	<p>When [SYSTEM MODE] = 59.94 Hz</p> <p>30p mode: 2, 15, 26, 28, 30, 32, 34, 45, 60 (fps)</p> <p>24p mode: 2, 12, 20, 22, 24, 26, 28, 36, 48, 60 (fps)</p> <p>SYSTEM MODE = 50.00, Hz</p> <p>25p mode: 2, 12, 21, 23, 25, 27, 30, 37, 50 (fps)</p>
Super-Slow Motion Recording	<p>When [SYSTEM MODE] = 59.94 Hz</p> <p>Shooting frame rate FHD 120 fps,</p> <p>Slow motion effect 1/4 speed (when 30p mode),</p> <p>1/5 speed (when 24p mode)</p> <p>When [SYSTEM MODE] = 50.00 Hz</p> <p>Shooting frame rate FHD 100fps,</p> <p>Slow motion effect 1/5 speed (when 25p mode)</p>
Sensitivity	<p>When [HIGH SENS.] mode</p> <p>F11 (2000 lx, 3200 K, 89.9 % reflect, 1080/59.94i)</p> <p>F12 (2000 lx, 3200 K, 89.9 % reflect, 1080/50i)</p>
Minimum Subject Illumination	<p>0.2 lx (F2.8, gain 18 dB, Manual slow shutter 1/25,</p> <p>When [HIGH SENS.] mode)</p>
Digital Zoom	2x/5x/10x, i.Zoom (max. 30x)
Lens Hood	Hood with lens cover
Memory Card Recorder	
Recording Media*1	SDHC memory card (4 GB to 32 GB), SDXC memory card (48 GB to 128 GB), UHS-I supported
Recording Slot	Slot x 2
System Format	59.94 Hz/50 Hz
Motion Picture Recording	Recording Format: MOV, MP4, AVCHD
Recording Mode	Please see page 07 for the Recording Format table.
Recording Time	Please see back cover for the Recording Time table.
2 Slot Functions	Relay, Simultaneous, Background*2, Dual codec
Still Picture Recording Mode	JPEG (DCF/Exif2.2)
Still Picture Recording	<p>Motion Picture Playback: 8.8M: 4096 x 2160 (17:9),</p> <p>8.3M: 3840 x 2160 (16:9), 2.1M: 1920 x 1080 (16:9),</p> <p>0.9M: 1280 x 720 (16:9)</p>

Digital Video	
Video Signal for External Output	8bit 4:2:2*3
Recording Video Signal	8bit 4:2:0
Video Compression Format	MPEG-4 AVC/H.264 High Profile (MOV/MP4/AVCHD)
Digital Audio	
Recording Audio Signal	48 kHz/16 bit 2CH
Audio Signal Format	LPCM (MOV/MP4), Dolby Digital (AVCHD)
Headroom	12 dB
Dual Codec	
Recording Method	MOV, MP4
Video Compression Format (Dual Codec)	MPEG-4 AVC/H.264 High Profile
Audio Signal Format (Dual Codec)	LPCM
Recording Format	Please see page 08 for the Dual Codec Recording table.
Recording Time (Dual Codec)	32 GB: Approx. 1 hour 20 min.(FHD 50Mbps) Approx. 8 hours 30 min.(FHD 8Mbps) 64 GB: Approx. 2 hour 40 min.(FHD 50Mbps) Approx. 17 hours 10 min.(FHD 8Mbps) 128 GB: Approx. 5 hours 20 min.(FHD 50Mbps) Approx. 35 hours(FHD 8Mbps)
Video Input/Output	
SDI Out	BNC x 1, 0.8 V [p-p], 75 Ω, 3 G/1.5 G, HD SDI, SD SDI supported Output format: 1080/59.94p LEVEL-A/50.00p LEVEL-A, 1080/29.97PsF/25.00PsF/24.00PsF/23.98PsF, 1080/59.94i/50.00i, 720/59.94p/50.00p, 480/59.94i, 576/50.00i
Video Output	AV connector x 1
HDMI	Type A connector x 1, VIERA Link not supported Output format: 2160/59.94p/50.00p/29.97p/25.00p/24.00p/23.98p, 1080/59.94p/50.00p/29.97p/25.00p/24.00p/23.98p/59.94i/50.00i, 720/59.94p/50.00p, 480/59.94p, 576/50.00p
Audio Input	
Built-in Microphone	Stereo microphone
XLR Input	XLR (3-pin) x 2 (INPUT1, INPUT2) Input high impedance, LINE/MIC/MIC+48V (switchable SW) LINE: +4 dBu/0 dBu (switchable menu) MIC: -40 dBu/-50 dBu/-60 dBu (switchable menu)
Audio Output	
SDI	2 ch (LPCM) switchable gain: 0 dB/-6 dB/-12 dB
HDMI (Audio Output)	2 ch (LPCM)
Audio Out	AV connector x 1, Output level: 600 Ω, 316 mV
Headphone	3.5 mm diameter stereo mini jack x 1
Speaker	20 mm diameter, round x 1
Other Input/Output	
Camera Remote	2.5 mm diameter super mini jack x1 (ZOOM, S/S) 3.5 mm diameter mini jack x1 (FOCUS, IRIS)
TC Preset In/Out	BNC x 1, Used as the input and output terminals Input: 1.0 V to 4.0 V [p-p] 10 KΩ Output: 2.0 V ± 0.5 V [p-p] low impedance
USB 3.0 (Host)	Standard-A connector, 9-pin, external media device connection*4, bus power supported
USB 3.0 (Device)	Micro-B connector, 10-pin, Mass storage function (read only)
DC In 12V	DC 12V (11.4V to 12.6V) EIAJ Type4
Monitor/Viewfinder	
LCD Monitor	3.5 type LCD color monitor; Approx. 1,150,000 dots
View Finder	0.39 type OLED (organic EL display) Approx. 2,360,000 dots, video display area: approx. 1,770,000 dots
Included Accessories	Battery (AG-VBR59), Battery charger (AG-BRD50), AC adaptor, Microphone holder kit, AC cable, Eye cup, Lens hood, INPUT terminal cap, Operating instructions
Note	*1: An SD memory card with a capacity of UHS Speed Class 3 (U3) is required to shoot videos with a bit rate of 100 Mbps or higher. An SDXC memory card with a capacity of 64 GB or more and UHS Speed Class 3 (U3) is required to shoot UHD 2160/59.94p/50.00p videos with a bit rate of 150 Mbps or higher. *2: It supports in record mode less than 50 Mbps. *3: Output of UHD/59.94p/50.00p becomes 8 bit 4:2:0. *4: External media devices with a capacity of below 32 GB or a capacity above 2 TB cannot be used.