

**"Offering high operability ideal for rental & staging, digital signage, education and corporate environments. 55"', 450 cd/m2, 24/7 operation, portrait mode display."**

## TH-55SF2

"Highly reliable 24/7 professional signage display. Offering high operability ideal for rental & staging, digital signage, education and corporate environments."

### Key Features


55", 450 cd/m2, 9,5 mm(T/R/L), 15.6mm(B) bezel width

High reliability enables continuous 24/7 operation with highly durable panel

System expandability - DVI daisy chain, built-in simple media player

Durable failover and fallback function with simplified workflow solution





## TH-55SF2

<https://eu.connect.panasonic.com/cz/en/products/professional-displays/th-55sf2>

<b>Screen Size</b>	55-inch (1387 mm)
<b>Panel Type</b>	LCD IPS Panel/E-LED
<b>Aspect Ratio</b>	16:9
<b>Effective Display Area (W x H)</b>	1209 x 680 mm (47.6" x 26.7")
<b>Number of Pixels (H x V)</b>	1920 x 1080 pixels
<b>Brightness</b>	450 cd/m2
<b>Contrast Ratio</b>	1100:1
<b>Dynamic Contrast</b>	50000:1
<b>Response Time</b>	12 ms (G to G)
<b>Viewing Angle (Horizontal/Vertical)</b>	178°/178°(CR≥10)
<b>Power Requirements</b>	110-127/220-240 V AC,50/60 Hz
<b>Power Consumption</b>	115W
<b>Power Off Condition</b>	Approx.0.3W
<b>Standby Condition</b>	Approx.0.5W
<b>Dimensions (W x H x D)</b>	1234 x 710 x 46 mm (48.5" x 28.0" x 1.8")
<b>Bezel Width</b>	T/R/L: 9.5 mm (0.38") B: 15.6 mm (0.62")
<b>Weight</b>	Approx. 18.0 kg(39.7 lbs.)
<b>Wall-Hanging Pitch</b>	VESA Compliant 400 x 400 mm(15.8" x 15.8")
<b>Operating Environment</b>	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
<b>Panel Surface Treatment</b>	Anti-Glare
<b>Haze</b>	1%