



"Offering high operability ideal for rental & staging, digital signage, education and corporate environments. 43"', 450 cd/m2, 24/7 operation, portrait mode display."

TH-43SF2

"Highly reliable 24/7 professional signage display. Offering high operability ideal for rental & staging, digital signage, education and corporate environments."

Key Features

43", 450 cd/m2, 9,5 mm(T/R/L), 15.6mm(B) bezel width

High reliability enables continuous 24/7 operation with highly durable panel

System expandability - DVI daisy chain, built-in simple media player

Durable failover and fallback function with simplified workflow solution





TH-43SF2

<https://eu.connect.panasonic.com/cz/en/products/professional-displays/th-43sf2>

Screen Size	43-inch (1079 mm)
Panel Type	LCD IPS Panel/E-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	941 x 529 mm (37.0" x 20.8")
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	450 cd/m2
Contrast Ratio	1100:1
Dynamic Contrast	50000:1
Response Time	12 ms (GtoG)
Viewing Angle (Horizontal/Vertical)	178°/178°(CR≥10)
Power Requirements	110-127/220-240 V AC,50/60 Hz
Power Consumption	95W
Power Off Condition	Approx.0.3W
Standby Condition	Approx.0.5W
Dimensions (W x H x D)	965 x 559 x 46 mm (38.0" x 22.0" x 1.8")
Bezel Width	T/R/L: 9.5 mm (0.38") B: 15.5 mm (0.61")
Weight	10.7 kg (23.6 lbs.)
Wall-Hanging Pitch	VESA Compliant 400 x 400 mm(15.8" x 15.8")
Operating Environment	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
Panel Surface Treatment	Anti-Glare
Haze	1%