



ET-WM200

Wireless module



ET-WM200

<https://eu.connect.panasonic.com/cz/en/products/projectors/et-wm200>

Power Supply	Supplied from the projector.
Standard	IEEE 802.11 a/b/g/n
Modulation	Direct sequence spread spectrum (DSSS) system, Orthogonal frequency division multiplex (OFDM) system
Modulation Techniques	DBPSK, DQPSK, CCK, BPSK, QPSK, 16QAM, 64QAM, MIMO
Transmission Speed (Standard)*1	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g/a: Up to 54 Mbps IEEE 802.11n: Up to 300 Mbps
Access Method	Infrastructure Mode
Security	WPA2-PSK(AES)
Interface	Mini USB 2.0 (Cannot be used with any projector other than a Panasonic projector with ET-WM300 compatibility.)
Dimensions (W x H x D) (mm)	102 x 8 x 31 mm
Dimensions (W x H x D) (inch)	4-1/32 inch x 5/16 inch x 1-7/32 inch
Weight	Approx. 13.5 g*(0.5 ozs)
Applicable Projector	PT-MZ670/MZ670L/MZ570/MZ570L/MW630/MW630L/MW530/MW530L
Note	*1 This is a theoretical speed. The actual transfer speed varies depending on the usage environment and connected devices. *2 Average value. May differ depending on models.