



Indoor pan tilt head

## AW-PH405

High performance indoor pan tilt head

### Key Features

---

High pan-tilt speed

---

Maximum load: 15 kg

---

Pan range: 300°, Tilt range: 300°

## AW-PH405

<https://eu.connect.panasonic.com/cz/en/products/broadcast-proav/aw-ph405>

<b>Power Supply/Power Consumption</b>	AC 120 V (60 Hz), AC 220 to 240 V (50 Hz) / 120 W
<b>Weight</b>	Approx. 10 kg (Approx. 22.0 lb)
<b>Dimensions (W x H x D) (Pan-Tilt Head only, Excluding Protrusions)</b>	319 mm x 416 mm x 168 mm (12-9/16 inches x 16-3/8 inches x 6-5/8 inches)
<b>Maximum Load (Including with a Camera, a Lens and a Teleprompter)</b>	Approx. 15 kg (Approx. 33.1 lb)
<b>Pan/Tilt Angle (Maximum Pan/Tilt Speed)</b>	Pan Approx. $\pm 150^\circ$ (45°/s) Tilt Approx. $\pm 150^\circ$ (45°/s)
<b>Stop Accuracy</b>	under $\pm 3$ arcminutes (0.05°)
<b>Quietness</b>	under NC35 (at 30°/s)
<b>Maximum Control Distance (when using AW-RP120G/AW-RP50)</b>	1000 m
<b>Interface RS232C</b>	-
<b>Maximum Preset Memories</b>	50
<b>Applicable Lens</b>	ENG lenses, MD lenses
<b>Tally Light</b>	Standard equipment (removable)
<b>Teleprompter Output</b>	Standard equipment
<b>Accessory</b>	Camera cable (Approx. 0.6 m)
<b>AC Adaptor/Power Cable</b>	AC adaptor built in (power cable (2 m) included)