



## High Resolution LCD Monitor

### BT-LH2170

Wide Viewing Angle Full-HD IPS Panel. High Performance and Rugged Durability with a Full-HD IPS Panel and 3D-LUT Picture Quality A 55 cm (21.5 inches) LCD Monitor with Excellent Cost-Performance for Broadcast Use.

#### Key Features

---

55 cm (21.5 inches) Wide Viewing Angle Full-HD (1920 x 1080) IPS Panel

---

High-Quality Imaging Engine

---

Tough and mobile



## BT-LH2170

<https://eu.connect.panasonic.com/cz/en/products/broadcast-proav/bt-lh2170>

<b>General</b>	
<b>Power Requirement</b>	AC 100 V to 240 V, 50 Hz/60 Hz, 0.55 A to 0.25 A DC 12 V (11 V to 17 V), 3.8 A
<b>Dimensions (W x H x D)</b>	510 mm x 388 mm x 198 mm (including stand) (20-1/16 inches x 15-1/4 inches x 7-13/16 inches) 510 mm x 373 mm x 72 mm (unit only, not including stand) (20-1/16 inches x 14-5/8 inches x 2-13/16 inches)
<b>Weight</b>	Approx. 7.0 kg (15.43 lb) (including stand) Approx. 6.1 kg (13.45 lb) (unit only, not including stand)
<b>Operating Temperature</b>	5 °C to 35 °C (41 °F to 95 °F)
<b>Operating Humidity</b>	20 % to 80 % (no condensation)
<b>Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>LCD Panle</b>	
<b>Panel Size</b>	550 mm (21.5 inches)
<b>Aspect Ratio</b>	16:9
<b>Resolution</b>	1,920 pixels x 1,080 pixels (FULL HD)
<b>Display Colors</b>	Approx. 16,770,000 colors
<b>Viewing Angle</b>	178° both horizontal and vertical (contrast >10:1)
<b>Connectors</b>	
<b>Video Input</b>	Video: BNC x 1 SDI: BNC x 2, SMPTE ST425/424/274/296/259/ITU-R BT.656-4 compliant, embedded audio supported 3G-SDI: SMPTE299M compliant, 48 kHz, 16 CH, synchronous supported HD SDI: SMPTE299M compliant, 48 kHz, 8 CH, synchronous supported SD SDI: SMPTE272M compliant, 48 kHz, 4 CH, synchronous supported HDMI: HDMI x 1 (TypeA), HDCP supported, embedded audio supported, VIERA Link not supported DVI-I: DVI-I x 1, HDCP supported, TMDS single link
<b>Video Output</b>	Video: BNC x 1, through-out (75 Ω auto) SDI: BNC x 2, active through-out
<b>Audio Input</b>	Pinjack x 2 (stereo)
<b>Headphone Output</b>	M3 stereo mini jack x 1
<b>Remote</b>	GPI: D-SUB, 9 pin RS-232C: D-SUB, 9 pin RS-485: RJ-45 x 2 (input, output)
<b>External DC Power Input</b>	XLR, 4 pin
<b>Signal Level</b>	
<b>Video</b>	HD/VD Signal level: TTL level
<b>Audio</b>	Audio input signal level: 0.31 Vrms Speaker output: 0.5 W, Monaural Head phone output: 32 Ω, Variable Level
<b>Others</b>	
<b>Supplied Accessories</b>	Power cord, Stand, Stand screw, Protective panel screw
<b>Optional Accessories</b>	Wall mount adaptor