



4K(UHD)/FHD-Camcorder mit Speicherkarte und integriertem Objektiv

AG-UX90

4K(UHD)/FHD-Camcorder mit branchenweit größtem 24,5mm-Weitwinkel*, 20-fach optischem Zoom und variabler Bildfrequenz

Key Features

LEICA DICOMAR-Objektiv mit 15-fach optischem Zoom und 24,5mm-Weitwinkel

1,0-Typ MOS-Sensor für hochpräzise Aufnahmen in UHD 25p oder FHD 50p

Intelligenter Autofokus unterstützt ruckfreie und schnelle Fokussierung bei Aufnahmen in 4K

Erweiterter optischer Bildstabilisator (OIS)

FHD-Aufzeichnung mit variabler Bildfrequenz (VFR) von 2 bis 50 fps





AG-UX90

<https://eu.connect.panasonic.com/de/products/broadcast-proav/ag-ux90>

General	
Power	DC 7.28 V (when the battery is used)
	DC 12 V (when the AC adaptor is used)
Power Consumption	12.2 W (when the LCD monitor is used)
Umgebungstemperatur	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10 % to 80 % (no condensation)
Gewicht	Body: Approx. 1.9 kg (4.19 lb)
	(body only, excluding lens hood, battery, and accessories)
	Shooting: Approx. 2.3 kg (5.07 lb)
Dimensionen	(including lens hood, battery, and eye cup)
	169 mm (W) x 195 mm (H) x 340 mm (D)
	(6-21/32 inches x 7-11/16 inches x 13-3/8 inches)
	(excluding protrusion and eye cup)
	169 mm (W) x 195 mm (H) x 382 mm (D)
(6-21/32 inches x 7-11/16 inches x 15-1/32 inches)	
(including eye cup, excluding protrusion)	
Camera Unit	
Pickup Devices	1.0-type MOS solid state image sensor
Effektive Pixel	17.78 megapixel: FHD 50.00p/25.00p
	8.59 megapixel: UHD 25.00p
Lens	Optical image stabilizer lens,
	optical 15x motorized zoom
	F2.8 to F4.5 (f=8.8 mm to 132 mm)
	35 mm equivalent:
	f=24.5 mm to 367.5 mm: FHD 50.00p/25.00p
	f=35.4 mm to 531.0 mm: UHD 25.00p
	Filter Diameter: 67 mm
	ND Filter: 4 Positions (OFF, 1/4, 1/16, 1/64)
	Shortest Shooting Distance (M.O.D.):
	Approx. 1.0 m from the front lens
Gain Setting	
L/M/H selector switch (toggle switch)	
Standard mode: 0 dB to 30 dB (Adjustable in 1 dB steps)	
(Automatic setting can be assigned to L/M/H)	
Extended ON: -3 dB to 30 dB (Adjustable in 1 dB steps)	
(Automatic setting can be assigned to L/M/H)	
33 dB and 36 dB switched	
(when assigning [S.GAIN] to the USER button)	
Color Temperature Setting	ATW, ATW LOCK, Ach, Bch, preset 3200 K/preset 5600 K/VAR (2000 K to 15000 K)
Verschlusszeit	50i/50p mode: 1/50 sec., 1/60 sec., 1/100 sec.,
	1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec.,
	1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec.,
	1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.
	25p mode: 1/25 sec., 1/50 sec., 1/60 sec., 1/100 sec.,
	1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec.,
	1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec.,
	1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.
	50i/50p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec., 1/25 sec.
	25p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec.
VFR Recording Frame Rate	25p mode: 2, 12, 21, 23, 25, 27, 30, 37, 50 (fps)
Minimum Subject Illumination	1.1 lx
	(F2.8, Super Gain 36dB, Manual slow shutter 1/25s)

Digitaler Zoom	2x/5x/10x, i.Zoom: max. 25x (optical zoom + digital zoom)
Lens Hood	Hood with lens cover
Memory Card Recorder	
Recording Media*1	SDHC memory card (4 GB to 32 GB), SDXC memory card (48 GB to 128 GB) UHS-I supported
Recording Slot	Slot x 2
System Format	50 Hz
Recording Format	MOV, MP4, AVCHD
Recording Mode	Please see page 1 for the Recording Format table.
Recording Time	Please see below for the Recording Time table.
2 Slot Functions	Relay, Simultaneous
Still Picture Recording Mode	JPEG (DCF/Exif2.2)
Still Picture Recording	Motion Picture Playback: 8.3 M: 3840 x 2160 (16:9), 2.1 M: 1920 x 1080 (16:9), 0.9 M: 1280 x 720 (16:9)
Digital Video	
Video Signal for External Output	8 bit 4:2:2
Recording Video Signal	8 bit 4:2:0
Video Compression Format	MPEG-4 AVC/H.264 High Profile (MOV/MP4/AVCHD)
Digital Audio	
Sampling Frequency	48 kHz/16 bit 2 ch
Audio Signal Format	LPCM (MOV/MP4), Dolby Audio (AVCHD)
Headroom	12 dB
Video Input/Output	
Video Output	VIDEO OUT connector x 1
HDMI	Type A connector x 1, VIERA Link not supported Output format: 2160/25.00p, 1080/50p/25p/50i, 720/50p, 576/50p
Audio Input	
Built-in Microphone	Stereo microphone
XLR Input	XLR (3-pin) x 2 (INPUT1, INPUT2) high impedance, LINE/MIC/MIC+48V (switchable SW) LINE: +4 dBu/0 dBu (switchable menu) MIC: -40 dBu/-50 dBu/-60 dBu (switchable menu)
Audio Output	
HDMI (Audio Output)	2 ch (LPCM)
Audio Out	AUDIO OUT x 2
Kopfhörer	3.5 mm diameter stereo mini jack x 1
Speaker	20 mm diameter, round x 1
Other Input/Output	
Camera Remote	2.5 mm diameter super mini jack x1 (ZOOM, S/S) 3.5 mm diameter mini jack x1 (FOCUS, IRIS)
USB 3.0 (Host)	Standard-A connector, 9-pin, external media device connection*2, bus power supported
USB 3.0 (Device)	Micro-B connector, 10-pin, Mass storage function (read only)
DC In 12V	DC 12 V (11.4 V to 12.6 V) EIAJ Type4
Monitor/Viewfinder	
LCD Monitor	3.5-type LCD color monitor, Approx. 1,150,000 dots
View Finder	0.24-type LCD EVF monitor, Approx. 1,560,000 dots equivalent
Included Accessories	Battery (AG-VBR59), Battery charger (AG-BRD50), AC adaptor, Microphone holder, Screw for microphone holder (12 mm), AC cable x 2, Eye cup, Lens hood, INPUT terminal cap, Operating instructions
Note	*1: An SD memory card with a capacity of UHS Speed Class 3 (U3) is required to shoot videos with a bit rate of 100 Mbps or higher. *2: External media devices with a capacity of below 32 GB or a capacity above 2 TB cannot be used.