



17.8cm / 7" LCD color viewfinder

## AK-HVF70G

The AK-HVF70E is a 17,8cm (7") LCD color viewfinder with light weight, low power consumption and a high resolution plus versatile assist functions like focus-in-red and pixel-to-pixel. By direct connect functionality no separate cable is necessary to connect the VF to the studio camera.

### Key Features

---

Resolution: 1024 x 600 (WSVGA)

---

Three assignable function keys

---

Focus assist functions (focus-in-red, pixel-to-pixel)

---

Tilt angle: 90° upward and 60° downward

---

Weight: 1,8kg

## AK-HVF70G

<https://eu.connect.panasonic.com/de/en/products/broadcast-proav/ak-hvf70g>

<b>Power Supply</b>	DC 12 V (supplied by the camera)
<b>Power Consumption</b>	10 W
<b>Operating Temperature</b>	0 °C to 45 °C (32 °F to 113 °F)
<b>Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>Operating Humidity</b>	10% to 85% (no condensation)
<b>Weight</b>	Approx. 1.6 kg (approx. 3.53 lb) (without hood)
<b>Dimensions (W x H x D)</b>	243.5 mm x 212 mm x 172 mm (9-19/32 inches x 8-11/32 inches x 6-25/32 inches) (with hood attached) 243.5 mm x 212 mm x 85 mm (9-19/32 inches x 8-11/32 inches x 3-11/32 inches) (without hood)
<b>Panel Size</b>	177.8 mm (7.0 inches)
<b>Number of Pixels</b>	1024 pixel x 600 pixel (WSVGA)
<b>Display Colors</b>	Approx. 16,200,000 colors
<b>Operation Panel</b>	POWER switch x 1, MENU button x 1 SELECT dial x 1, Function buttons x 3 Picture adjusting knobs x 3 ([BRIGHT], [CONTRAST], [PEAKING])
<b>Connectors</b>	Camera I/F connector (D-Sub 29-pin x 1)