



Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 75", 400 cd/m², stylish design display with narrow bezel and IPS panel for clear off-axis visibility

TH-75CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

Key Features

75", 400 cd/m²

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

IPS Panel for superb viewing experience from any angle

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





TH-75CQ1

<https://eu.connect.panasonic.com/de/en/products/professional-displays/th-75cq1>

Screen size (diagonal) (inch)	74.7-inch
Screen size (diagonal) (mm)	1898 mm
Aspect Ratio	16:9
Panel Type	IPS Panel / Direct-LED
Effective display area (W x H) (mm)	1654 x 932 mm
Effective display area (W x H) (inch)	36.1" x 36.6"
Resolution	3840 x 2160
Brightness (typ.)	400 cd/m2
Contrast Ratio	1400 : 1
Response Time	8 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR>10)
Terminals HDMI In	HDMI Type A Connector x 2
Terminals PC IN/AUDIO IN (L/R)	Mini D-Sub 15-pin (DDC2B) x 1
Terminals Serial	D-sub 9pin x 1, RS-232C Compatible
Terminals Audio Out	RCA Terminal (L / R) x 1
Terminals LAN	RJ45 x 1
Terminals USB	USB Type A Connector x 1, DC 5 V/0.5 A (USB 2.0 is supported)
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	AC 110 - 127 V 50 Hz / 60 Hz
Power Consumption	274 W
Power Off Condition	Approx. 0.5 W
Standby Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1684 x 969 x 94 mm
Dimensions (W x H x D) (inch)	66.3" x 38.1" x 3.7"
Bezel width (mm)	T/R/L 14.9 mm) B 18.4 mm
Bezel width (inch)	T/R/L 0.59" B 0.73"
Weight (kg)	Approx. 34 kg
Weight (lbs.)	Approx. 75.0 lbs
Wall-hanging pitch (mm)	VESA Compliant 400 x 400 mm (Installed by: M6 screws / Screw hole depth (18 mm)
Wall-hanging pitch (inch)	VESA Compliant 15.7" x 15.7" (Installed by: M6 screws / Screw hole depth 0.7"
Operating Time	16 h/day
Operating Environment	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation)