



Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 65", 400 cd/m², stylish design display with narrow bezel and VA/LED panel for clear off-axis visibility

TH-65CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

Key Features

65", 400 cd/m²

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

VA/LED Panel for superb viewing experience from any angle

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





TH-65CQ1

<https://eu.connect.panasonic.com/de/en/products/professional-displays/th-65cq1>

Screen size (diagonal) (inch)	64.5-inch
Screen size (diagonal) (mm)	1638 mm
Aspect Ratio	16:9
Panel Type	VA / Direct-LED
Effective display area (W x H) (mm)	1428 x 803 mm
Effective display area (W x H) (inch)	56.2" x 31.6"
Resolution	3840 x 2160
Brightness (typ.)	400 cd/m2
Contrast Ratio	5000 : 1
Response Time	8 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR≥20)
Terminals HDMI In	HDMI TYPE-A Connector x 2
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1
Terminals Serial	D-sub 9-pin x 1 (Input, RS-232C Compatible)
Terminals Audio Out	Pin Jack x 1
Terminals LAN	RJ45 x 1, 10 BASE-T / 100 BASE-TX
Terminals USB	USB Connector (TYPE-A) x 1, DC 5V/0.5A (USB 2.0 Supported)
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	AC 110 - 127 V 50 Hz / 60 Hz
Power Consumption	136w
Power Off Condition	Approx. 0.5 W
Standby Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1463 x 847 x 97 mm
Dimensions (W x H x D) (inch)	57.6" x 33.4" x 3.8"
Bezel width (mm)	T/R/L 15.9 mm B 19.9 mm
Bezel width (inch)	T/R/L 0.63" B 0.78"
Weight (kg)	Approx.33 kg
Weight (lbs.)	Approx. 72.8 lbs
Wall-hanging pitch (mm)	400 x 200 mm VESA compliant
Wall-hanging pitch (inch)	VESA Compliant 15.7" x 7.9" (400 x 200 mm) (Installed by: M6 screws / Screw hole depth 0.7" (17 mm))
Operating Time	16 h/day
Operating Environment	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation)