



Thin and stylish design offering high level digital signage with easy installation and high connectivity. Ideal for corporate and retail environments. 55", 350 cd/m² narrow bezel and IPS panel for excellent visibility.

TH-55EQ1

55" 4K professional entry-level digital display. Featuring a thin and stylish design offering high level digital signage with easy installation and high connectivity. Ideal for corporate and retail environments.

Key Features

55", 350 cd/m²

4k ultra HD resolution delivering the highest detail and image quality. Non-4K sources are also beautifully compensated.

Simple signage with built in USB media player. Synchronized playback on multiple displays via USB and LAN.

Extensive connectivity features. 4K/60p video input signals via 2 x HDMI. Supports CEC over HDMI® for power on/off.

Easy set up and safe operation. Failover and Failback function for any unexpected troubles. Monitoring of multi-displays can be done through the free Multi Monitoring & Control software.



Media
Player





TH-55EQ1

<https://eu.connect.panasonic.com/dk/en/products/professional-displays/th-55eq1>

| | |
|--|---|
| Screen size (diagonal) (inch) | 55-inch |
| Screen size (diagonal) (mm) | 1387 mm |
| Aspect Ratio | 16:9 |
| Panel Type | VA Panel/D-LED |
| Effective display area (W x H) (mm) | 1209 x 680 mm |
| Effective display area (W x H) (inch) | 47.6 x 26.7 inch |
| Resolution | 3840 x 2160 |
| Brightness (typ.) | 350 cd/m2 |
| Contrast Ratio | 4000:1 |
| Response Time | 8 ms (G to G) |
| Viewing angle [(T/B)/(L/R)] | 178° / 178° (CR≥10) |
| Panel Surface Treatment | Anti-glare type (Haze 2%) |
| Terminals HDMI In | HDMI TYPE-A Connector x 2 (HDCP2.2 supported) |
| Terminals Video/AV In | 4-pole Mini Jack (M3) x 1 (Audio: Stereo Mini Jack (M3) x 1(Shared with DVI-D/PC In)) |
| Terminals DVI-D IN/AUDIO IN (L/R) | DVI-D 24-pin x 1, DVI Revision 1.0 Compatible (HDCP 1.1 supported) / Stereo Mini Jack (M3) x 1 (Shared with Video/PC In) |
| Terminals PC IN/AUDIO IN (L/R) | Mini D-sub 15-pin x 1 (Compatible with DDC 2B) / Stereo Mini Jack (M3) x 1 (Shared with Video/DVI-D In) |
| Terminals USB | USB Connector (TYPE A) x 1, DC 5 V/2 A (USB 3.0 supported) |
| Terminals Audio Out | Stereo Mini Jack (M3) x 1 / Variable Output (-∞ - 0 dB) (at 1 kHz 0 dB Input, 10 kΩ Loaded) |
| Terminals Serial | D-sub 9-pin x 1 (Input), RS-232C Compatible |
| Terminals LAN | RJ45 x 1, 10BASE-T/100BASE-TX/1000BASE-T, Compatible with PLink™ |
| Terminals IR In/Out | Stereo Mini Jack (M3) x 1 / x 1 |
| Built-in Speaker | 20 W [10 W + 10 W] |
| Power Requirements | 110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz |
| Power Consumption | 195 W |
| Power Off Condition | Approx. 0.3 W |
| Standby Condition | Approx. 0.5 W |
| Dimensions (W x H x D) (mm) | 1240 x 712 x 62 mm |
| Dimensions (W x H x D) (inch) | 48.9 x 28.1 x 2.5 inch |
| Bezel width (mm) | 12.9 mm (T/R/L), 14.7 mm (B) |
| Bezel width (inch) | 0.6" (T/R/L), 0.6" (B) |
| Weight (kg) | Approx. 17 kg |
| Weight (lbs.) | 37.5 lbs. |
| Wall-hanging pitch (mm) | 400 x 200 mm VESA Compliant |
| Wall-hanging pitch (inch) | 15.8 x 7.9 inch VESA Compliant |
| Orientation | Landscape/Portrait |
| Tilting angle | 0-20 degrees forward/backward with landscape/portrait setting |
| Operating Time | 18 h/day |
| Operating Environment | 0°C to 40°C (32°F to 104°F) / for up to 1400 m (4593 ft) altitude, 0°C to 35°C (32°F to 95°F) / Altitude 1400-2800 m [4593 ft to 9186 ft] |