



**Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 75", 400 cd/m<sup>2</sup>, stylish design display with narrow bezel and IPS panel for clear off-axis visibility**

## TH-75CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

### Key Features

---

75", 400 cd/m<sup>2</sup>

---

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

---

IPS Panel for superb viewing experience from any angle

---

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

---

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation

---





## TH-75CQ1

<https://eu.connect.panasonic.com/dk/en/products/professional-displays/th-75cq1>

<b>Screen size (diagonal) (inch)</b>	74.7-inch
<b>Screen size (diagonal) (mm)</b>	1898 mm
<b>Aspect Ratio</b>	16:9
<b>Panel Type</b>	IPS Panel / Direct-LED
<b>Effective display area (W x H) (mm)</b>	1654 x 932 mm
<b>Effective display area (W x H) (inch)</b>	36.1" x 36.6"
<b>Resolution</b>	3840 x 2160
<b>Brightness (typ.)</b>	400 cd/m2
<b>Contrast Ratio</b>	1400 : 1
<b>Response Time</b>	8 ms (G to G)
<b>Viewing angle [(T/B)/(L/R)]</b>	178° / 178° (CR>10)
<b>Terminals   HDMI In</b>	HDMI Type A Connector x 2
<b>Terminals   PC IN/AUDIO IN (L/R)</b>	Mini D-Sub 15-pin (DDC2B) x 1
<b>Terminals   Serial</b>	D-sub 9pin x 1, RS-232C Compatible
<b>Terminals   Audio Out</b>	RCA Terminal (L / R) x 1
<b>Terminals   LAN</b>	RJ45 x 1
<b>Terminals   USB</b>	USB Type A Connector x 1, DC 5 V/0.5 A (USB 2.0 is supported)
<b>Built-in Speaker</b>	20 W [10 W + 10 W]
<b>Power Requirements</b>	AC 110 - 127 V 50 Hz / 60 Hz
<b>Power Consumption</b>	274 W
<b>Power Off Condition</b>	Approx. 0.5 W
<b>Standby Condition</b>	Approx. 0.5 W
<b>Dimensions (W x H x D) (mm)</b>	1684 x 969 x 94 mm
<b>Dimensions (W x H x D) (inch)</b>	66.3" x 38.1" x 3.7"
<b>Bezel width (mm)</b>	T/R/L 14.9 mm) B 18.4 mm
<b>Bezel width (inch)</b>	T/R/L 0.59" B 0.73"
<b>Weight (kg)</b>	Approx. 34 kg
<b>Weight (lbs.)</b>	Approx. 75.0 lbs
<b>Wall-hanging pitch (mm)</b>	VESA Compliant 400 x 400 mm (Installed by: M6 screws / Screw hole depth (18 mm)
<b>Wall-hanging pitch (inch)</b>	VESA Compliant 15.7" x 15.7" (Installed by: M6 screws / Screw hole depth 0.7"
<b>Operating Time</b>	16 h/day
<b>Operating Environment</b>	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation)