



Indoor pan tilt head

AW-PH405

High performance indoor pan tilt head

Key Features

High pan-tilt speed

Maximum load: 15 kg

Pan range: 300°, Tilt range: 300°

AW-PH405

<https://eu.connect.panasonic.com/dk/en/products/broadcast-proav/aw-ph405>

Power Supply/Power Consumption	AC 120 V (60 Hz), AC 220 to 240 V (50 Hz) / 120 W
Weight	Approx. 10 kg (Approx. 22.0 lb)
Dimensions (W x H x D) (Pan-Tilt Head only, Excluding Protrusions)	319 mm x 416 mm x 168 mm (12-9/16 inches x 16-3/8 inches x 6-5/8 inches)
Maximum Load (Including with a Camera, a Lens and a Teleprompter)	Approx. 15 kg (Approx. 33.1 lb)
Pan/Tilt Angle (Maximum Pan/Tilt Speed)	Pan Approx. $\pm 150^\circ$ (45°/s) Tilt Approx. $\pm 150^\circ$ (45°/s)
Stop Accuracy	under ± 3 arcminutes (0.05°)
Quietness	under NC35 (at 30°/s)
Maximum Control Distance (when using AW-RP120G/AW-RP50)	1000 m
Interface RS232C	-
Maximum Preset Memories	50
Applicable Lens	ENG lenses, MD lenses
Tally Light	Standard equipment (removable)
Teleprompter Output	Standard equipment
Accessory	Camera cable (Approx. 0.6 m)
AC Adaptor/Power Cable	AC adaptor built in (power cable (2 m) included)