



**65-inch class highly reliable professional display with 4K resolution that is ideal for corporate meeting rooms, educational, and signage applications.**

## TH-65SQE2

The Panasonic Connect TH-65SQE2W 4K Professional Display is designed for 16-hour continuous operation and crystal-clear viewing clarity. The display provides a brightness of 500cd/m<sup>2</sup> with an anti-glare panel, and minimum haze treatment of 25%, reducing the reflection of ambient light and vastly improving visibility in all environments. For ultimate flexibility and a clean look without set-top-boxes or cables, the TH-65SQE2W is also equipped with a slot for the Intel® SDM specification supporting applications, such as digital signage and broadcasts, using a built-in PC, terminal board, or wireless presentation system.

### Key Features

High image quality and high legibility suitable for various scenes

Superb Reliability & Easy Installation

Various external linkage suitable for conference room and signage applications





## TH-65SQE2

<https://eu.connect.panasonic.com/es/en/products/professional-displays/th-65sqe2>

<b>Panel   Panel size</b>	65-inch class (64.52-inch/1638.9 mm)
<b>Panel   Effective display area (W x H)</b>	1428.4 x 803.5 mm (56.23" x 31.63")
<b>Panel   Resolution</b>	3840 x 2160
<b>Panel   Brightness (typ.)</b>	500 cd/m2
<b>Panel   Contrast</b>	1200:1
<b>Panel   Viewing angle [(T/B)/(L/R)]</b>	178°/178° (CR>10)
<b>Panel   Panel surface treatment</b>	Anti-glare (Haze 25 %)
<b>Terminals   HDMI™ IN</b>	HDMI™ x 4 (compatible with HDCP2.2)
<b>Terminals   HDMI™ OUT</b>	HDMI™ x 1 (compatible with HDCP2.2)
<b>Terminals   DisplayPort IN</b>	DisplayPort x 1 (compatible with HDCP2.2)
<b>Terminals   USB</b>	Type A: DC 5 V/max. 0.9 A, USB 3.0 is supported, Type A: DC 5 V/max. 0.5 A, USB 2.0 is supported, Type A: DC 5 V/max. 0.5 A, USB 2.0 is supported (Internal), Type C: DC 5 V/max. 3.0 A, USB 3.0 is supported, DisplayPort Alternate mode compatible
<b>Terminals   microSD</b>	microSD/SDHC/SDXC / MAX 1 TB
<b>Terminals   Serial In</b>	Stereo mini jack (φ3.5 mm) x 1, RS-232C Compatible
<b>Terminals   LAN</b>	RJ45 x 1, compatible with PLink™ 10BASE-T/100BASE-TX/1000BASE-T
<b>Terminals   IR In</b>	Stereo mini jack (φ3.5 mm) x 1
<b>Terminals   Slot</b>	Intel® SDM standard , Supply power for SLOT 66W
<b>Terminals   Wi-Fi</b>	Yes (Built-in)
<b>Terminals   Bluetooth®</b>	Yes (Built-in)
<b>Terminals   Audio Out</b>	Stereo mini jack (φ3.5 mm) x 1, SPDIF x 1
<b>HTML browser</b>	HTML5 (Vwed)
<b>Android™-OS</b>	Yes
<b>Operating time*1</b>	24 h/day
<b>Orientation</b>	Landscape/Portrait
<b>Tilt angle*2</b>	0-45 degrees forward and backward withlandscape/portrait setting
<b>Built-in Speaker</b>	20 W
<b>Power Supply</b>	AC 110-240 V50 Hz/60 Hz, 3.5 A-1.8 A
<b>Power Consumption</b>	170 W (Shipping Condition)
<b>On Mode Average Power Consumption*3</b>	165 W (Picture Mode: [Natural])
<b>Power off condition/Stand-by condition</b>	Approx. 0 W / Approx. 0.5 W
<b>Energy efficiency class</b>	G
<b>Dimension (WxHxD) (Excluding remote IR sensor)</b>	1456 x 835 x 96 mm(57.32" x 32.84" x 3.78")
<b>Weight</b>	24.9 kg/54.9 lbs
<b>Bezel Width</b>	12.9mm (0.51") (T/R/L), 16.1mm (0.63") (B)
<b>Wall-Hanging Pitch</b>	600 x 400 mm, M6
<b>Operating Environment</b>	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)
<b>Note</b>	*1: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.*2: Please contact your sales representative with regard to the tilt angle before installation. *3: Based on IEC 62087 Ed.2 measurement method.