



"Offering high operability ideal for rental & staging, digital signage, education and corporate environments. 49"', 450 cd/m2, 24/7 operation, portrait mode display."

TH-49SF2

"Highly reliable 24/7 professional signage display. Offering high operability ideal for rental & staging, digital signage, education and corporate environments."

Key Features

49", 450 cd/m2, 9,5 mm(T/R/L), 15.6mm(B) bezel width

High reliability enables continuous 24/7 operation with highly durable panel

System expandability - DVI daisy chain, built-in simple media player

Durable failover and fallback function with simplified workflow solution





TH-49SF2

<https://eu.connect.panasonic.com/es/en/products/professional-displays/th-49sf2>

Screen Size	49-inch (1232 mm)
Panel Type	LCD IPS Panel/E-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1073 x 604 mm (42.2" x 23.7")
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	450 cd/m2
Contrast Ratio	1100:1
Dynamic Contrast	50000:1
Response Time	12 ms (G to G)
Viewing Angle (Horizontal/Vertical)	178°/178° (CR≥10)
Power Requirements	110-127/220-240 V AC,50/60 Hz
Power Consumption	110W
Power Off Condition	Approx.0.3W
Standby Condition	Approx.0.5W
Dimensions (W x H x D)	1098 x 634 x 46 mm (43.2" x 24.9" x 1.8")
Bezel Width	T/R/L: 9.5 mm (0.38") B: 15.5 mm (0.61")
Weight	14.7 kg(32.4 lbs.)
Wall-Hanging Pitch	VESA Compliant 400 x 400 mm(15.8" x 15.8")
Operating Environment	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
Panel Surface Treatment	Anti-Glare
Haze	1%