



Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 86", 400 cd/m², stylish design display with narrow bezel and IPS panel for clear off-axis visibility.

TH-86CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

Key Features

86", 400 cd/m²

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

IPS Panel for superb viewing experience from any angle

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





TH-86CQ1

<https://eu.connect.panasonic.com/es/en/products/professional-displays/th-86cq1>

| | |
|--|---|
| Screen size (diagonal) (inch) | 86-inch |
| Screen size (diagonal) (mm) | 2177.4 mm |
| Aspect Ratio | 16:9 |
| Panel Type | IPS Panel / Edge LED |
| Effective display area (W x H) (mm) | 1897 x 1068 mm |
| Effective display area (W x H) (inch) | 74.70 x 42.00 inch |
| Resolution | 3840 x 2160 |
| Brightness (typ.) | 400 cd/m2 |
| Contrast Ratio | 1200 : 1 |
| Response Time | 8 ms (G to G) |
| Viewing angle [(T/B)/(L/R)] | 178° / 178° (CR>10) |
| Terminals HDMI In | HDMI TYPE-A Connector x 2 |
| Terminals PC IN/AUDIO IN (L/R) | Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1 |
| Terminals Serial | D-sub 9-pin x 1 (Input), RS-232C Compatible |
| Terminals Audio Out | RCA Terminal (L / R) x 1 |
| Terminals LAN | RJ45 x 1, 10BASE-T/100BASE-TX |
| Terminals USB | USB Type A Connector x 1, DC 5 V/0.5 A (USB 2.0 is supported) |
| Built-in Speaker | 20 W [10 W + 10 W] |
| Power Requirements | AC 110 - 127 V 50 Hz / 60 Hz |
| Power Consumption | 340 W |
| Power Off Condition | Approx. 0.5 W |
| Standby Condition | Approx. 0.5 W |
| Dimensions (W x H x D) (mm) | 1929 x 1103 x 80 mm |
| Dimensions (W x H x D) (inch) | 76.0" x 43.5" x 3.2" |
| Bezel width (mm) | (T/B/L/R) 15.3 mm |
| Bezel width (inch) | T/B/L/R 0.61" |
| Weight (kg) | Approx. 50 kg |
| Weight (lbs.) | Approx. 110.3 lbs |
| Wall-hanging pitch (mm) | VESA Compliant 600 x 400 mm |
| Wall-hanging pitch (inch) | VESA Compliant 23.6" x 15.7" |
| Operating Time | 16 h/day |
| Operating Environment | Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation) |