



La serie CQE1 con resolución 4K es compatible con la señal 4K/60p y puede funcionar durante 24 horas al día (98") o 16 horas al día (43-86"). La pantalla CQE1 dispone de una amplia gama de terminales de conexión y también de las funciones necesarias para el uso comercial.

TH-75CQE1

Imágenes con un alto grado de detalle en resolución 4K (3840×2160) que admiten señales de vídeo 4K de 60p para una fiel representación de contenido de alta calidad. Permite un funcionamiento continuo ininterrumpido (98") o 16 horas al día, 7 días a la semana (43-86"), sin ningún problema. Ideal para el uso diario en oficinas, escuelas y otras aplicaciones. Dispone de cuatro terminales de entrada HDMI compatibles con HDMI CEC. La serie CQE1 es un terminal USB de tipo C que dispone de una pantalla que puede conectarse a un PC o una tablet. También compatible con Crestron Connected™.

Key Features

75", 400 cd/m² y visión nítida con revestimiento antirreflectante

La pantalla LCD 4K UHD ofrece un contenido muy detallado con ajustes de contraste que mejoran la calidad de imagen

Diseño elegante y moderno con marco fino y sencilla instalación, con altavoces integrados y terminales básicos

Dispone de cuatro terminales de entrada HDMI compatibles con HDMI CEC





TH-75CQE1

<https://eu.connect.panasonic.com/es/es/products/professional-displays/th-75cqe1>

Screen size [diagonal] (inch)	75-inch class(1892.7 mm)
Panel Type	D-LED
Aspect Ratio	16:9
Effective display area (W x H) (mm)	1649.6 x 927.9 mm
Effective display area (W x H) (inch)	64.94" x 36.53"
Resolución	3840 x 2160
Brightness (typ.)	400 cd/m2
Contrast Ratio	1200:1
Response Time	8.0 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR>10)
Panel Surface Treatment	Anti-glare low reflection type (Haze 1%)
Terminals HDMI In	HDMI TYPE-A Connector x 4
Terminals PC In	Mini D-sub 15-pin x 1 (Female)
Terminals Serial	D-sub 9-pin x 1 (Female), RS232C Compatible
Terminals IR In	Stereo Mini Jack (M3) x 1
Terminals Audio In	Pin jack x 2 (L/R)
Terminals Audio Out	Stereo Mini Jack (M3) x 1, SPDIF×1
Terminal LAN	RJ45 x 1
Terminals USB	USB Connector Type-A x 2, Type-C x 1, (Internal) Type-A x 1
Wi-Fi	Built-in, IEEE 802.11. a/b/g/n/ Dual Wi-Fi CERTIFIED
Built-in Speaker	24 W [12 W + 12 W]
Power Requirements	110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz
Power Consumption	307 W
Power Off Condition	0 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1684 x 968 x 100 mm *Excluding remote IR sensor
Dimensions (W x H x D) (inch)	66.28" x 38.09" x 3.92" *Excluding remote IR sensor
Weight (kg)	Approx. 36.8 kg
Weight (lbs.)	81.2 lbs
Bezel width (mm)	15.7 mm (T/R/L), 21.5 mm (B)
Bezel width (inch)	0.62" (T/R/L), 0.85" (B)
Wall-hanging pitch (mm)	VESA Compliant 600 x 400 mm
Wall-hanging pitch (inch)	VESA Compliant 23.6" x 15.8"
Orientation	Landscape (Not support to the portrait installation)
Tilting angle*1	0-20 degree forward
Operating time*2	16 h/day
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

Note *1: Please contact your sales representative with regard to the tilt angle before installation.

*2: Displaying a still image for a long time may cause burn-in (image persistence artifacts), it could be mitigated when display video image.