



Equipped with advanced professional features offering a slim, lightweight, and scalable solution which simplifies any installations. 98", 4K Ultra HD panel, Intel® Smart Display Module (Intel® SDM), 24/7 operation, portrait, 4K Digital link, narrow bezel

TH-98SQ1

98" 4K professional and stylish digital display. Equipped with advanced professional features including Intel Smart Display Module and offering a slim, lightweight, and scalable solution which simplifies any installations.

Key Features

98", 500 cd/m², 4K IPS panel with slim and stylish design and 24/7 operation

High image quality through HDR support (HLG system) that displays light and dark images in a realistic way

4K USB Media Player: eliminates the need for external devices and allows updates via LAN

High expandability with ultra-slim Intel® SDM (Intel® Smart Display Module), DisplayPort connection for daisy-chain signage, multiple screen function (quad, PinP, PbyP) and 4K DIGITAL LINK

Flexible and light installation either in portrait or landscape



Media
Player





TH-98SQ1

<https://eu.connect.panasonic.com/en/products/professional-displays/th-98sq1>

Screen size (diagonal) (inch)	98-inch (2477 mm)
Screen size (diagonal) (mm)	2477 mm
Aspect Ratio	16:9
Panel Type	IPS Panel/ Direct-LED
Effective display area (W x H) (mm)	2158.8 x 1214.3 mm
Effective display area (W x H) (inch)	84.9 x 47.8 inch
Resolution	3840 x 2160
Brightness (typ.)	500 cd/m2
Contrast Ratio	1300:1 (Typ)
Response Time	8 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178°/178° (CR≥10)
Panel Surface Treatment	Anti-Grare Type (Haze 28%)
Terminals HDMI In	HDMI TYPE-A Connector x 2
Terminals DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with PC In)
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)
Terminals DisplayPort IN	DisplayPort x 1
Terminals DisplayPort OUT	DisplayPort x 1
Terminals USB	USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)
Terminals Serial	D-sub 9-pin x 1, RS-232C Compatible
Terminal LAN	RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™
Terminal DIGITAL LINK	RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™
Terminals Slot	Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A
Terminals IR IN / OUT	Stereo Mini Jack (M3) x 1 / x 1
Terminals Audio Out	30 W [15 W + 15 W] 10% THD
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	110-240 V AC, 50 Hz/60 Hz
Power Consumption	685 W
Power Off Condition	Approx. 0.3 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	2194 x 1249 x 90 mm
Dimensions (W x H x D) (inch)	86.4" x 49.2" x 3.5"
Bezel width (mm)	16.0 mm (T/B/L/R)
Bezel width (inch)	0.63 inch (T/B/L/R)
Weight (kg)	Approx. 90.0 kg
Weight (lbs.)	Approx. 198.5 lbs
Gross Weight (kg)	Approx. 138.0 kg
Gross Weight (lbs.)	Approx. 304.3 lbs
Wall-hanging pitch (mm)	800 x 500 mm VESA Compliant
Wall-hanging pitch (inch)	31.5 x 19.7 inch VESA Compliant
Orientation	Landscape / Portrait
Tilting angle	Landscape setting: 0 - 20 degrees forward/backward Portrait setting: 0 - 20 degrees forward/backward
Operating Time	24 h/day
Operating environment Temperature	0 °C to 40 °C
Operating Environment Humidity	20% to 80% (Non-condensation)