



The PT-RZ990 Series delivers the brightness, resolution, and colour that designers need to enhance exhibits with bright, bold, and vivid pictures

## PT-RZ790

Deepen immersion in any environment with vivid, accurate colours backed by up to 10,000 lm\*1 of brightness thanks to Quartet Colour Harmonizer and 1-Chip DLP™ imaging technology. With support for 4K/60p input signals, separate DIGITAL LINK and LAN terminals, and diverse optional lenses, these projectors reduce installation hassles with convenient flexibility. Engineered for 20,000 hours of maintenance-free reliability with lasting brightness and colour uniformity from the industry's leading dust-resistant optical engine.

### Key Features

Laser 1-chip DLP, 7,200 lm (center)/7,000 lm (ANSI), WUXGA

Quartet Colour Harmonizer technology for more accurate colour reproduction

Maintenance free up to 20,000 hours with dust-resistant optical block and long lasting laser engine

Supports 4K/60p Signal Input, separate DIGITAL LINK and LAN terminals





## PT-RZ790

<https://eu.connect.panasonic.com/fi/en/products/projectors/pt-rz790>

|   |  |
|---|--|
| <b>Screen size [diagonal]</b>   | 1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:10 aspect ratio  |
| <b>Center-to-corner zone ratio*1</b>  | 90 %   |
| <b>Lens</b>   | With supplied lens: Powered zoom (throw ratio 1.71–2.41:1), powered focus F 1.7–1.9, f 25.6–35.7 mm Without lens: Optional powered zoom/focus lenses   |
| <b>Lens shift*4   Vertical(From the origin point of the lens mounter)</b>   | +50 %, -16 % (+40 %, -16 % with ET-DLE060) (powered)   |
| <b>Lens shift*4   Horizontal(From the origin point of the lens mounter)</b> | +30 %, -10 % (+10 %, -20 % with ET-DLE020, +19 %, -10 % with ET-DLE060, +28 %, -10 % with ET-DLE105/ET-DLE085) (powered)   |
| <b>Keystone Correction Range</b>  | Vertical: ±40 ° (±5 ° with ET-DLE020, ±16 ° with ET-DLE060, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055, +5 ° with ET-DLE035), Horizontal: ±15 ° (±10 ° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)   |
| <b>Keystone correction range with optional ET-UK20 Upgrade Kit</b>          | Vertical: ±45 ° (±16 ° with ET-DLE060, ±40 ° with ET-DLE150/ET-DLE250/ET-DLE170, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055), Horizontal: ±40 ° (±10 ° with ET-DLE060, ±15 ° with ET-DLE105/ET-DLE085/ET-DLE055) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.  |
| <b>Terminals   SDI In</b>   | BNC x 1: 3G/HD/SD-SDI input  |
| <b>Terminals   HDMI In</b>  | HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input*5)  |
| <b>Terminals   DVI-D In</b>   | DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)   |
| <b>Terminals   RGB 1 In</b>   | RGB x 1 (BNC x 5): RGB/YBPBR/YCBCR   |
| <b>Terminals   RGB 2 In</b>   | D-sub HD 15-pin (female) x 1: RGB/YBPBR/YCBCR  |
| <b>Terminals   Serial/Multi Projector Sync In</b>                           | D-sub 9-pin (female) x 1 for external control (RS-232C compliant)  |
| <b>Terminals   Serial/Multi Projector Sync Out</b>                          | D-sub 9-pin (male) x 1 for link control  |
| <b>Terminals   REMOTE 1 IN</b>  | M3 x 1 for wired remote control  |
| <b>Terminals   REMOTE 1 OUT</b>   | M3 x 1 for link control (for wired remote control)   |
| <b>Terminals   Remote 2 In</b>  | D-sub 9-pin (female) x 1 for external control (parallel)   |
| <b>Terminals   DIGITAL LINK</b>   | RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input*5   |
| <b>Terminals   LAN</b>  | RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible   |
| <b>Power Supply</b>   | AC 100–240 V, 50/60 Hz   |
| <b>Power Consumption</b>  | 545 W (Normal)/435 W (Eco)/ 215 W (Long Life 1)/195 W (Long Life 2)/ 170 W (Long Life 3)   |
| <b>Operation noise*1</b>  | 36 dB (Normal)   |
| <b>Dimensions (W x H x D)</b>   | With supplied lens: 498 x 200*6 x 581 mm (19 19/32" x 7 7/8" *6 x 22 7/8") Without lens: 498 x 200*6 x 538 mm (19 19/32" x 7 7/8" *6 x 21 3/16")   |
| <b>Weight*7</b>   | With supplied lens: Approx. 22.1 kg (48.7 lbs)<br>Without lens: Approx. 21.3 kg (47.0 lbs)   |
| <b>Operating Environment</b>  | Operating temperature: 0–45 °C (32–113 °F)*8, operating humidity: 10–80 % (no condensation)  |
| <b>Applicable Software</b>  | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™   |
| <b>Note</b>   | *1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. *3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [ON], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m3 of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *4 Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE035. *5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI @.*6 Excluding legs. *7 Average value. May differ depending on the actual unit. |
| <b>Resolution</b>   | 1920 x 1200 pixels   |
| <b>Contrast Ratio*1</b>   | 10,000:1 (Full On/Full Off, Dynamic Contrast [3])  |
| <b>Light Source</b>   | Laser diodes   |
| <b>DLP™ Chip   Panel Size</b>   | 17.0 mm (0.67 in) diagonal (Panel size 16:10 aspect ratio)   |
| <b>DLP™ Chip   Display Method</b>   | DLP™ chip x 1, DLP™ projection system  |
| <b>Light output</b>   | 7,000 lm (Normal)*1 / 7,200 lm (Center)*2 / 5,600 lm (Eco)*1 / 2,800 lm (Long Life 1)*1 / 2,300 lm (Long Life 2)*1 / 1,900 lm (Long Life 3)*1  |
| <b>Projector type</b>   | 1-Chip DLP™ projector  |
| <b>DLP™ chip   Number of Pixels</b>   | 2,304,000 (1920 x 1200 pixels)   |
| <b>Time until light output declines to 50 %*3</b>                           | 20,000 hours (Normal)/24,000 hours (Eco)   |

