



**High cost-to-performance display for professional users seeking a 4K video wall solution. 49" frameless D-LED LCD, 450 cd/m<sup>2</sup>, 3.5 mm bezel to bezel, 24/7 operation, portrait mode, anti-glare surface and robust display.**

## TH-49LFV8

Highly reliable frameless video wall display. High cost-to-performance video wall for professional users seeking a 4K video-wall solution.

### Key Features

49", 450 cd/m<sup>2</sup>, 3,5 mm bezel to bezel, anti-glare surface


DisplayPort UHD daisy chain functionality

A super narrow frame for optimal multi-screen layouts.

Ideal for installation in standard indoor places, wide colour viewing angle and high visibility

450 cd/m<sup>2</sup>

24/7  
Operation



## TH-49LFV8

<https://eu.connect.panasonic.com/fr/en/products/professional-displays/th-49lfv8>

<b>Screen Size</b>	49-inch (1237 mm)
<b>Panel Type</b>	LCD IPS Panel/D-LED
<b>Aspect Ratio</b>	16:9
<b>Effective Display Area (W x H)</b>	1077 x 607 mm(42.5" x 24.0")
<b>Number of Pixels (H x V)</b>	1920 x 1080 pixels
<b>Brightness</b>	450 cd/m2
<b>Contrast Ratio</b>	1400:1
<b>Response Time</b>	8 ms(G to G)
<b>Viewing Angle</b>	178°/178° (CR≥10)
<b>Panel Surface Treatment</b>	Anti-Glare Low-Reflection (Haze 3%)
<b>Power Requirements</b>	110-240 V AC, 50/60 Hz
<b>Power Consumption</b>	220 W
<b>Standby Condition</b>	Approx. 0.5 W
<b>Dimensions (W x H x D)</b>	1077.7 x 607.9 x 103.9 mm(42.5" x 24.0" x 4.1")
<b>Bezel Width</b>	L/T:2.25 mm(0.088"),R/B:1.25 mm(0.049")
<b>Weight</b>	Approx.22.0kg(48.5 lbs) TBD
<b>Wall-Hanging Pitch</b>	VESA compliant 400 x 400 mm(15.8" x 15.8")