

Panasonic
CONNECT



HD Monitor with 3D Capability

BT-3DL2550

Superb HD Display Performance and 3D Capability



BT-3DL2550

<https://eu.connect.panasonic.com/fr/en/products/broadcast-proav/bt-3dl2550>

Power Supply	24 V DC, 4.5 A
Weight	Approx. 10.3 kg (22.7 lb) (including stand)
Operating Temperature	5 °C to 35 °C (41 °F to 95 °F)
Operating Humidity	20% to 80% (no condensation)
Storage Temperature	0°C to 60 °C (-4 °F to 140 °F)
Size	647,7 mm / 25.5 inches
Aspect Ratio	16:10
Resolution	1920 pixels _ 1200 pixels (WUXGA)
Display Colors	Approx. 16,770,000 colors
Viewing Angle	178° both of horizontal and vertical (in 2D Mode, at contrast >10:1)
Panel Surface	Xpol™ polarizing panel
Audio Input	Pin jack _ 2 (stereo): Signal level 0.5 Vrms
Headphone Output	Stereo mini-jack M3 _ 1, 32 Ω, adjustable level
GPI	D-SUB 9-pin _ 1
RS-232C	D-SUB 9-pin _ 1
External DC Power Input	XLR 4 pins _ 1 (for supplied AC adapter)
Video System	SYNC signal level: 0.3 V [p-p] to 4.0 V [p-p]
Audio System	AUDIO Input signal level: 0.5 Vrms
HD SDI	SMPTE299M standard, 48 kHz,
Standard Accessories	3D Polarized Eyewear (BT-PGL10G) _ 2, AC Adaptor (DC cable attachment), Power cable, Power cable hook, Screw (for securing power cable)
Optional Units	BT-PGL10G 3D Polarized Eyewear
Dimensions (W x D x H)	599 mm × 440 mm × 220 mm (23-5/8 inches × 17-5/16 inches × 8-11/16 inches) (including stand) 599 mm × 410 mm × 100 mm (23-5/8 inches × 16-1/8 inches × 3-15/16 inches) (not including stand) AC Adaptor : 232 mm × 50.5 mm × 177 mm (9-1/8 inches × 2 inches × 6-15/16 inches)
Video	BNC × 1, through out (automatic, 75 Ω termination)
SDI	BNC × 2, active through out
YPBPR/RGB	BNC × 3, through out (automatic, 75 Ω termination)
Sync/HD	BNC × 1, through out (automatic, 1 kΩ termination)
VD	BNC × 1, through out (automatic, 1 kΩ termination)
DVI-D	DVI-D × 1, HDCP compatible, TMDS single link Vertical frequency: 50.0 Hz to 60.0 Hz Horizontal frequency: 31.5 kHz to 67.5 kHz Dot clock: 25 MHz to 165 MHz