



High Resolution LCD Monitor

BT-LH2170

Wide Viewing Angle Full-HD IPS Panel. High Performance and Rugged Durability with a Full-HD IPS Panel and 3D-LUT Picture Quality A 55 cm (21.5 inches) LCD Monitor with Excellent Cost-Performance for Broadcast Use.

Key Features

55 cm (21.5 inches) Wide Viewing Angle Full-HD (1920 x 1080) IPS Panel

High-Quality Imaging Engine

Tough and mobile



BT-LH2170

<https://eu.connect.panasonic.com/fr/en/products/broadcast-proav/bt-lh2170>

General	
Power Requirement	AC 100 V to 240 V, 50 Hz/60 Hz, 0.55 A to 0.25 A DC 12 V (11 V to 17 V), 3.8 A
Dimensions (W x H x D)	510 mm x 388 mm x 198 mm (including stand) (20-1/16 inches x 15-1/4 inches x 7-13/16 inches) 510 mm x 373 mm x 72 mm (unit only, not including stand) (20-1/16 inches x 14-5/8 inches x 2-13/16 inches)
Weight	Approx. 7.0 kg (15.43 lb) (including stand) Approx. 6.1 kg (13.45 lb) (unit only, not including stand)
Operating Temperature	5 °C to 35 °C (41 °F to 95 °F)
Operating Humidity	20 % to 80 % (no condensation)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
LCD Panel	
Panel Size	550 mm (21.5 inches)
Aspect Ratio	16:9
Resolution	1,920 pixels x 1,080 pixels (FULL HD)
Display Colors	Approx. 16,770,000 colors
Viewing Angle	178° both horizontal and vertical (contrast >10:1)
Connectors	
Video Input	Video: BNC x 1 SDI: BNC x 2, SMPTE ST425/424/274/296/259/ITU-R BT.656-4 compliant, embedded audio supported 3G-SDI: SMPTE299M compliant, 48 kHz, 16 CH, synchronous supported HD SDI: SMPTE299M compliant, 48 kHz, 8 CH, synchronous supported SD SDI: SMPTE272M compliant, 48 kHz, 4 CH, synchronous supported HDMI: HDMI x 1 (TypeA), HDCP supported, embedded audio supported, VIERA Link not supported DVI-I: DVI-I x 1, HDCP supported, TMDS single link
Video Output	Video: BNC x 1, through-out (75 Ω auto) SDI: BNC x 2, active through-out
Audio Input	Pinjack x 2 (stereo)
Headphone Output	M3 stereo mini jack x 1
Remote	GPI: D-SUB, 9 pin RS-232C: D-SUB, 9 pin RS-485: RJ-45 x 2 (input, output)
External DC Power Input	XLR, 4 pin
Signal Level	
Video	HD/VD Signal level: TTL level
Audio	Audio input signal level: 0.31 Vrms Speaker output: 0.5 W, Monaural Head phone output: 32 Ω, Variable Level
Others	
Supplied Accessories	Power cord, Stand, Stand screw, Protective panel screw
Optional Accessories	Wall mount adaptor