



Unité de type 1/4 de rack prenant en charge le
contrôle PoE+ et IP

AK-HRP1000

Panneau de commande à distance de type 1/4 de rack prenant en
charge le contrôle PoE+ et IP

Key Features

Écran de mesure LCD en couleur permettant la contrôle par
interface graphique utilisateur ainsi que par PoE+ et IP

Master Gain, température de couleur et Master Flare variables
pouvant être assignés à un bouton utilisateur programmable

Manette de commande pour contrôler l'iris / la poursuite

Peut être utilisé avec un mélange de caméras studio et à
distance Panasonic par connexion IP



AK-HRP1000

<https://eu.connect.panasonic.com/fr/fr/products/broadcast-proav/ak-hrp1000>

Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC)
	42 V - 57 V DC (PoE power supply)
Power Consumption	0.51 A (Power supply from camera: 10 V - 16 V DC)
	0.15 A (PoE power supply)
Température de fonctionnement	0°C to 40°C (32°F to 104°F)
Humidity	90% or less
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Poids	Approx. 1.7 kg (3.75 lb)
Dimensions (W x H x D)	102 mm x 385 mm x 113 mm
	(4 inches x 15-3/16 inches x 4-7/16 inches)
Camera/CCU Control	Control signals (camera, CCU control)
	Power supply 16 V DC (when CCU connected)*4,
	12 V DC (when camera connected)*4
Maximum Cable Length	When camera connected: 20 m (65.7 ft)
	When CCU connected: 50 m (164 ft)
Compatibility	-
Note	<p>*1: Depending on the setting, only one of them can be selected at one time.</p> <p>*2: The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically.</p> <p>*3: IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF].</p> <p>*4: Can be provided from CCU</p>