



10.1" fully rugged Windows 11 Pro Tablet

TOUGHBOOK G2 mk3 standard

The TOUGHBOOK G2 is the next generation rugged device for mobile workforces. It offers all the benefits of the latest technology, while maintaining important access to legacy systems. All of this, wrapped up in a more flexible, secure and ultimately even more useable device.

Key Features

Intel® Core™ Ultra5 processor 135U (with Intel vPro Technology)

Windows 11 Pro

10.1" Active Matrix (TFT) colour LCD 1920 \times 1200 (WUXGA) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to $1.000cd/m^2$), IP55 Digitiser

IP65 Water and dust resistant****, Tested against MIL-STD 810H****

Long battery life of up to 15 hours (Mobile Mark™ 25) with extended Battery









TOUGHBOOK G2 mk3 standard

EVOLVED TO ADAPT

An evolution of the best-selling Panasonic Toughbook G1 tablet and 20 detachable, this latest tablet is powered by the Intel Core™ Ultra5 processor 135U (with Intel vPro Technology), delivering incredible performance, and is shipping with Windows 11 Pro. It also has a rich set of business interfaces with additional customisable options to meet a worker's needs. With its long battery life and outdoor viewing, glove-enabled touchscreen, it's a versatile yet tough technology companion for mobile workers.

Panasonic Connect GmbH, Mobile Solutions Business Division, Hagenauer Straße 43, 65203 Wiesbaden, Germany

https://eu.connect.panasonic.com/g b/en/toughbook/toughbook-g2series/toughbook-g2-mk3-standard







Model	FZ-G2mk3 Standard, 16GB RAM, 512GB SSD, standard battery pack, IP55 digitiser pen
Operating System	Windows 11 Pro
Mobile Computing Platform	Intel® CoreTM Ultra5 processor 135U (with Intel vPro® Technology)
Fraphic Chip	Intel® Graphics (Built-in CPU)
RAM	16GB (max. 32GB) DDR5x
Storage	512GB OPAL NVMe SSD (up to 2TB optional)
LCD	10.1" Active Matrix (TFT) colour LCD 1920 x 1200 (WUXGA) LCD with sunlight-viewable
	glove enabled capacitive touchscreen (up to 1.000cd/m²), IP55 Digitiser
Wireless	Mobile Broadband*: 4G or 5G with SIM/eSIM support Wireless
	LAN: Intel® Wi-Fi6E AX211
	GPS*: U-Blox NEO-M9N Series (not compatible to 5G model)
	LAN: IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-
	TBluetooth™: 5.3 Class 1 Mobile
Interfaces	USB 3.2 Gen 1 Type A: x1
	Thunderbolt 4: x1
	LAN: x1
	Dual Antenna Connector: x1
Rear expansion area	Smart Card Reader, HF-RFID (NFC) Reader, Fingerprint Reader***
op Expansion Area	Serial, 2D Barcode Reader, 2nd USB 2.0, 2nd LAN, Thermal by FLIR, Micro-SD**
ront Camera	2 MP with IR / privacy shutter (Windows Hello compliant)
lear Camera	13mpixel with autofocus and LED flash
ound	Intel® High Definition Audio subsystem support, Stereo speaker
Security	TPM (TCG V2.0 compliant), Integrated hardware security lock slot, Windows Hello
	compliant Webcam
(eyboard & Input (Keyboard)	x1*
Pointing device: Touchscreen (Touch panel)	Touchpad
Dimensions: Main Unit + Keyboard	287 mm x 235 mm x 52.7 mm / 11.3" x 9.3" x 2.1" (without protruding parts)
(WxHxD)	270 400 225 444.0% 7.4% 4.0% (1)
Dimensions: Main Unit (WxHxD)	279mm x 188mm x 23.5 mm / 11.0" x 7.4" x1.0" (without protruding parts)
Weight: Main Unit	Approx. 1.19kg / 2.64lb
Battery Life	Standard: Approx 11 hours (Mobile Mark™ 25) Extended: Approx 15 hours (Mobile Mark™ 25)
Power Supply: AC Adaptor	Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05 A
ower Supply: Battery	Standard: Li-ion 11.4V, 4360mAh (50Whr), Extended: Li-ion 10.8V, 6300mAh (68Whr)
Power Supply: Hot Swap	Standby function,
	ACPI BIOS,
	Hot swap optional
	Hot swap optional
Orop resistance	MIL-STD 810H, 180cm ****
·	• •
Oust resistance	MIL-STD 810H, 180cm ****
Dust resistance Water resistance	MIL-STD 810H, 180cm **** IEC529 (JIS C0920) IP6x ****
Dust resistance Nater resistance Operating temperature	MIL-STD 810H, 180cm **** IEC529 (JIS C0920) IP6x **** IEC529 (JIS C0920) IPx5 ****
Dust resistance Water resistance Operating temperature Included in the box	MIL-STD 810H, 180cm **** IEC529 (JIS C0920) IP6x **** IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual
Drop resistance Dust resistance Water resistance Operating temperature Included in the box Integrated options Footnote Description	MIL-STD 810H, 180cm **** IEC529 (JIS C0920) IP6x **** IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C ****

TOUGHBOOK G2 mk3 Standard: September 2024

Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances.

Sections 13.4, 13.6.2, 14.2.5 and 14.3

**** Tested by an independent third party lab following MIL-STD-810H and IEC 60529,