



Compact Camera & Recorder System with Versatile Operation for Broadcasting, Video Production, Live Streaming and more

AG-UMR20 & AG-UCK20

The "POVCAM" combines the advantages of the first-generation POVCAM with features that are necessary in today's environment like a touch panel and simultaneous 3G-SDI/HDMI/IP output. The POVCAM can be used as an unite or the recorder alone .

Key Features

Close-up face shots in TV Program Production

At indoor events (e.g. weddings, reality TV shows)

For nature observations, documentaries, sports and webcasts

As a back-up unit for a camera-recorder

For recording and networking from an information Camera

AVCHD
Progressive

HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE

SD
XCTM



AG-UMR20 & AG-UCK20

https://eu.connect.panasonic.com/gb/en/products/broadcast_proav/ag-umr20-ag-uck20

General	
Power	DC 7.28 V (with battery), DC 12 V (with AC adaptor) Camera Head: DC 9 V (supplied from the AG-UMR20)
Power Consumption	In standalone condition: 1.1 A (with battery), 0.7 A (with AC adaptor) With the optional AG-UCK20GJ Camera Head: 2.2 A (with battery), 1.4 A (with AC adaptor) Camera Head only: 0.6 A
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10 % to 80 % (no condensation)
Weight	Approx. 590 g (1.3 lbs) + Approx. 325 g (0.717 lbs)
Dimensions (W x H x D)	100 mm x 53.5 mm x 104 mm(excluding protrusion) (3-15/16 inches x 2-3/32 inches x 5-1/2 inches) + 64 mm x 72 mm x 131 mm (excluding protrusion) (2-17/32 inches x 2-27/32 inches x 5-5/32 inches)
Memory Card Recorder	
Recording Media	SDHC memory card (4 GB to 32 GB), SDXC memory card (48 GB to 128 GB) MP4: more than Class10, AVCHD: more than Class4
Recording Slot	2 Slots
System Format	59.94 Hz / 50.00 Hz
Motion Recording	Recording system: MP4, AVCHD Recording mode/Recording time: Please see page 3 for the "Recording Format" table
Still Picture Recording	Recording system: JPEG (DCF/Exif2.2)
Digital Video/Digital Audio	
Output Video Signal	8 bit 4:2:2
Recording Video Signal	8 bit 4:2:0
Video Compression	MP4: MPEG-4, AVCHD: AVC/H.264 High Profile
Recording Audio Signal	48 kHz/16 bit 2 CH
Audio Compression	MP4: LPCM, AVCHD: Dolby Audio
Headroom	12 dB
Video Input/Output	
SDI In	BNC x 1, 0.8 V [p-p], 75 Ω, 3 G/1.5 G HD SDI supported Input format:1080/59.94p LEVEL-A/LEVEL-B, 1080/50p LEVEL-A/LEVEL-B, 1080/29.97PsF/25PsF/23.98PsF, 1080/59.94i/50i, 720/59.94p/50p
SDI Out (Video)	BNC x 1, 0.8 V [p-p], 75 Ω, 3 G/1.5 G HD SDI supported Output format: same as input format
HDMI Out (Video)	Type A connector x 1, VIERA Link not supported Output format: 2160/29.97p/25p/23.98p, 1080/59.94p/50p/29.97p/25p/23.98p/59.94i/50i, 720/59.94p/50p, 480/59.94p, 576/50p
Audio Input/Output	
MIC/Line Input	3.5 mm diameter, stereo mini jack (MIC IN and LINE IN) MIC: -60 dBV (sensitivity -40 dB equivalent, 0 dB=1 V/Pa 1 kHz), plug in power supported LINE: -10 dBV
SDI Out (Audio)	2 CH (LPCM), switchable gain: 0 dB/-6 dB/-12 dB
HDMI Out (Audio)	2 CH (LPCM)
Headphone	3.5 mm diameter, stereo mini jack x 1
Speaker	20 mm diameter, round x 1
External Terminal	
Camera	20 pin dedicated interface
LAN	IP control LAN connector (RJ-45) Straight/cross cable auto-detect function
Remote	2.5 mm diameter stereo mini jack x 1 (ZOOM, S/S) 3.5 mm diameter mini jack x 1 (FOCUS, IRIS)
USB 2.0	Type Mini-B connector, mass storage (read/write)

DC In 12V	DC 12 V (11.4 V to 12.6 V) EIAJ Type4
Monitor	
LCD Monitor	3.5-type LCD monitor, approx. 1,150,000 dots
Network	
Video Compression (Network)	MP4:MPEG-4, AVCHD:AVC/H.264 High Profile
Audio Compression (Network)	AAC-LC (48kHz, 16 bit, 2 CH, 128 kbps)
Transfer Mode (JPEG)	Resolution 640 x 360: (JPEG) Frame rate (59.94 Hz): 30 fps, 15 fps, 5 fps Frame rate (50.00 Hz): 25 fps, 12.5 fps, 5 fps
Transfer Mode (H.264)	Resolution 3840 x 2160/640 x 360: (H.264) Frame rate (59.94 Hz): 30 fps, 15 fps, 5 fps Frame rate (50.00 Hz): 25 fps, 12.5 fps, 5 fps Resolution 1920 x 1080/1280 x 720: Frame rate (59.94 Hz): 60 fps, 30 fps, 15 fps, 5 fps Frame rate (50.00 Hz): 50 fps, 25 fps, 12.5 fps, 5 fps *By the conditions, the frame rate is lower than setting.
Supported Protocol	TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, DHCP, DNS, NTP, IGMP, UPnP, ICMP, ARP, RTSPoverTCP, RTSPoverHTTP, SSL (TLS), MultiCast/UniCast
IP Connector Cable	LAN cable* (more than category 5) max. 100 m *STP (Shielded Twisted Pair) recommend
Supported OS	
Windows	Microsoft(R) Windows 10 (32 bit/64 bit), Internet Explorer 11 Microsoft(R) Windows 7 (32 bit/64 bit) SP1, Internet Explorer 11
Mac	MacOS v10.12 Safari10, OS X v10.11 Safari10
Supported Browser	
iOS Device	iPhone/iPad/iPod touch, iOS 10, standard browser
Android	Android OS 4.4, standard browser
Supported Controller	
Controller	AW-RP50, AW-RP120G, AK-HRP200G *Depending on a model, upgrade is required.
Pickup Devices	1/2.3-type MOS MOS solid state image sensor (Total pixels: approx. 12.76 megapixels)
Lens	Zoom: optical 20x motorized zoom Fvalue: F1.8 to F3.6, Focal length: f- 4.08 mm to 81.6 mm 35 mm conversion: 29.5 mm to 612.0 mm (Hybrid O.I.S mode "OFF") Filter diameter: 49 mm, ND filter: CLEAR, 1/4, 1/16, 1/64 (built-in) Shortest shooting distance: 1.5 m (4.9 ft) at zoom range, 3 cm (0.1 ft) at wide angle IR cut filter : incorporates the ON/OFF control function
Zoom	i. Zoom: x30 (HD), x22 (4K) Digital zoom: x1.4, x2, x4, x6, x8
Image Stabilizer	Optical image stabilizer (HD/4K) 5-Axis hybrid image stabilizer (HD)
Gain Setting	Automatic, manual 0 dB to 30 dB(1 dB step), Super Gain 33 dB, 36 dB *At auto mode, 3 dB to 30 dB (3 dB steps) can be selected with AGC limit setting.
White Balance	ATW, ATW LOCK, AWB A, AWB B, P3200K, P5600K, VAR (2000 K to 15000 K)
Shutter Speed	59.94i/59.94p mode: 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec. 29.97p mode: 1/30 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec. to 1/8000 sec. (same as above) 23.98p mode: 1/24 sec., 1/48 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/120 sec., 1/180 sec. to 1/8000 sec. (same as above) 50i/50p mode: 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec. to 1/8000 sec. (same as above) 25.00p mode: 1/25 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec. to 1/8000 sec. (same as above)

Slow Shutter	59.94i/59.94p mode: 1/2 sec., 1/4 sec., 1/8 sec., 1/15 sec., 1/30 sec. 29.97p mode: 1/2 sec., 1/4 sec., 1/8 sec., 1/15 sec. 23.98p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec. 50i/50p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec., 1/25 sec., 25.00p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec.
Synchro Scan	59.94i/59.94p mode: 1/60.0 sec. to 1/285.6 sec. 29.97p mode: 1/30.0 sec. to 1/206.5 sec. 23.98p mode: 1/24.0 sec. to 1/280.1 sec. 50i/50p mode: 1/50.0 sec. to 1/209.2 sec. 25p mode: 1/25.0 sec. to 1/224.3 sec.
Minimum Illumination	0.2 lx (slow shutter: 1/2 sec., gain: +36 dB)
Horizontal Resolution	1,300 TV (HDMI output 2160/29.97p, when 25.00p playback) 1,000 TV (HDMI output 1080/59.94p, when 50.00p playback)
Audio In	Built-in microphone (2 CH stereo)
Connector	20 pin dedicated interface (to the AG-UMR20)