



## Remote Operation Panel (ROP)

# AK-HRP1000

1/4-type rack size remote operation panel which supports PoE+ and IP control

### Key Features

1/4-type rack size remote operation panel

Colour LCD readout display allows GUI operation, and also supports PoE+ and IP control

Variable master gain, colour temperature and master flare can all be assigned to a user knob

Joystick control lever allows Iris/Pedestal operation

Can be used with a mix of studio and Panasonic remote control cameras via IP connection



## AK-HRP1000

<https://eu.connect.panasonic.com/global/en/broadcast-proav/accessories/ak-hrp1000>

<b>General -&gt; Power Supply</b>	12 V DC (Power supply from camera: 10 V - 16 V DC)
	42 V - 57 V DC (PoE power supply)
<b>General -&gt; Power Consumption</b>	0.51 A (Power supply from camera: 10 V - 16 V DC)
	0.15 A (PoE power supply)
<b>General -&gt; Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>General -&gt; Operating Humidity</b>	90 % or less
<b>General -&gt; Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>General -&gt; Weight</b>	Approx. 1.7 kg (3.75 lb)
<b>General -&gt; Dimensions</b>	W 102 mm x H 385 mm x D 113 mm
	(4 inches x 15-3/16 inches x 4-7/16 inches)
<b>General -&gt; Camera/CCU Control</b>	Control signals (camera, CCU control)
	Power supply 16 V DC (when CCU connected) <sup>*1</sup> ,
	12 V DC (when camera connected) <sup>*1</sup>
<b>General -&gt; Maximum Cable Length</b>	When camera connected: 20 m (65.7 ft)
	When CCU connected: 50 m (164 ft)

### Footnote Description

Can be provided from CCU.