



17.8cm / 7" LCD color viewfinder

## AK-HVF70G

The AK-HVF70E is a 17,8cm (7") LCD color viewfinder with light weight, low power consumption and a high resolution plus versatile assist functions like focus-in-red and pixel-to-pixel. By direct connect functionality no separate cable is necessary to connect the VF to the studio camera.

### Key Features

Resolution: 1024 x 600 (WSVGA)

Three assignable function keys

Focus assist functions (focus-in-red, pixel-to-pixel)

Tilt angle: 90° upward and 60° downward

Weight: 1,8kg

## AK-HVF70G

<https://eu.connect.panasonic.com/hu/en/broadcast-proav/accessories/ak-hvf70g>

<b>General -&gt; Power Supply</b>	DC 12 V (supplied from camera)
<b>General -&gt; Power Consumption</b>	10 W
<b>General -&gt; Operating Temperature</b>	0 °C to 45 °C (32 °F to 113 °F)
<b>General -&gt; Operating Humidity</b>	10% - 85% (no condensation)
<b>General -&gt; Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>General -&gt; Weight</b>	Approx. 1.6 kg (3.53 lbs.) (not including hood)
<b>General -&gt; Dimensions</b>	W 243.5 mm x H 212 mm x D 172 mm
	(9-19/32 inches x 8-11/32 inches x 6-25/32 inches)
	(with hood attached)
	W 243.5 mm x H 212 mm x D 85 mm
	(9-19/32 inches x 8-11/32 inches x 3-11/32 inches)
	(without hood)
<b>Display Panel -&gt; Dimensions</b>	177.8 mm (7.0 inches)
<b>Display Panel -&gt; Number of Pixels</b>	1024 x 600 (WSVGA)
<b>Display Panel -&gt; Display Color</b>	Approx. 16,2 million colors
<b>Switch Functions and Connectors -&gt; Operation</b>	<POWER> switch, <MENU> button, <SELECT> dial button, <F1>/<F2>/<F3> buttons, <BRIGHT> knob, <CONTRAST> knob, <PEAKING> knob
<b>Switch Functions/Connectors -&gt; Connector</b>	Camera I/F connector (D-sub 29 pins x 1)