



Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 55", 400 cd/m<sup>2</sup>, stylish design display with narrow bezel and VA/LED panel for clear off-axis visibility.

## TH-55CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

### Key Features

55", 400 cd/m<sup>2</sup>

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

VA/LED Panel for superb viewing experience from any angle

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





## TH-55CQ1

<https://eu.connect.panasonic.com/hu/en/products/professional-displays/th-55cq1>

<b>Screen size (diagonal) (inch)</b>	54.6-inch
<b>Screen size (diagonal) (mm)</b>	1387 mm
<b>Aspect Ratio</b>	16:9
<b>Panel Type</b>	VA Panel / D-LED
<b>Effective display area (W x H) (mm)</b>	1209 x 680
<b>Effective display area (W x H) (inch)</b>	47.6" x 26.7"
<b>Resolution</b>	3840 x 2160
<b>Brightness (typ.)</b>	400 cd/m2
<b>Contrast Ratio</b>	4000 : 1
<b>Response Time</b>	8 ms (G to G)
<b>Viewing angle [(T/B)/(L/R)]</b>	178° / 178° (CR≥20)
<b>Terminals   HDMI In</b>	HDMI Type A Connector x 2
<b>Terminals   PC IN/AUDIO IN (L/R)</b>	Mini D-Sub 15-pin (DDC2B) x 1
<b>Terminals   Serial</b>	D-sub 9pin x 1, RS-232C Compatible
<b>Terminals   IR Out</b>	Pin Jack x 1
<b>Terminals   Audio Out</b>	RCA Terminal (L / R) x 1
	Variable (-∞ - 0 dB)(1 kHz 0 dB Input, 10 kΩ Load)
	0.5 V [rms]
<b>Terminals   LAN</b>	RJ45 x 1
	RJ45 10BASE-T/100BASE-TX
<b>Terminals   USB</b>	USB Type A Connector x 1, DC 5 V/0.5 A (USB 2.0 is supported)
<b>Built-in Speaker</b>	20 W [10 W + 10 W]
<b>Power Requirements</b>	AC 110 - 127 V 50 Hz / 60 Hz
<b>Power Consumption</b>	128 W
<b>Power Off Condition</b>	Approx. 0.5 W
<b>Standby Condition</b>	Approx. 0.5 W
<b>Dimensions (W x H x D) (mm)</b>	1240 x 718 x 80 mm
<b>Dimensions (W x H x D) (inch)</b>	48.9" x 28.3" x 3.2"
<b>Bezel width (mm)</b>	T/R/L 11.9 mm B 14.7 mm
<b>Bezel width (inch)</b>	T/R/L 0.47" B 0.59"
<b>Weight (kg)</b>	Approx. 15 kg
<b>Weight (lbs.)</b>	Approx. 33.1 lbs
<b>Wall-hanging pitch (mm)</b>	VESA Compliant (400 x 200 mm) (Installed by: M6 screws / Screw hole depth (17 mm))
<b>Wall-hanging pitch (inch)</b>	VESA Compliant 15.7" x 7.9" (Installed by: M6 screws / Screw hole depth 0.7")
<b>Operating Time</b>	16 h/day
<b>Operating Environment</b>	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2
	Humidity : 20% to 80% (No condensation)