



## **ET-D3LEW200**

The Zero Offset Ultra Short Throw Fixed-Focus Lens is designed for compatibility with RZ21 series, RZ31 series projectors.



## ET-D3LEW200

<https://eu.connect.panasonic.com/hu/en/products/projectors/et-d3lew200>

|                                  |  |
|----------------------------------|--|
| <b>Lens type</b>                 | Short-Throw Zoom Lens  |
| <b>F Value</b>                   | 2.5  |
| <b>Focal Length</b>              | 13.8-18.1 mm (17/32"-23/32")   |
| <b>Screen Size</b>               | 200-600 inches   |
| <b>Throw ratio   4K+</b>         | 0.693-0.913:1  |
| <b>Throw ratio   WUXGA</b>       | 0.645-0.850:1  |
| <b>Throw ratio   SXGA+</b>       | 0.699-0.921:1  |
| <b>Lens-shift*1   Vertical</b>   | ±59 %  |
| <b>Lens-shift*1   Horizontal</b> | ±19 %  |
| <b>Zoom</b>                      | Yes  |
| <b>Dimensions (W×H×D)</b>        | 250 × 193 × 495 mm (9 27/32" x 7 19/32" x 19 1/2")   |
| <b>Weight</b>                    | Approx. 9.0 kg (19.8 lbs)  |
| <b>Compatible projectors</b>     | RQ32K/RZ31K Series/RQ22K/RZ21K Series  |
| <b>Note</b>                      | * Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: <a href="https://panasonic.net/cns/projector/calculator/tdc/">https://panasonic.net/cns/projector/calculator/tdc/</a> . For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value. |