



Camera Adaptor

AG-CA300

This new camera studio system boosts the level of cost-performance for a wide range of P2 HD and DVCPRO HD camera-recorders. BNC cables transmit degradation-free HD digital images up to 328' (100 meters). Plus, in addition to giving you full remote control of camera functions and recording, the system supplies power to the camera and provides return images and signals including mic of intercom. The ability to operate with both AC and DC power brings camera extension system recording to a variety of studio and field applications.

Key Features

Digital signal transmission ensures high-quality, degradation-free images

The compact, lightweight design boosts shoulder-held mobility

Allows the use of Anton, IDX and other batteries



AG-CA300

<https://eu.connect.panasonic.com/hu/en/products/broadcast-proav/ag-ca300>

Power Supply	Input: DC 24 V, 4 A DC 12V, 6 A Output: DC 13 V, 5 A
Weight	Main unit: 2.9 lbs (1.3 kg) Battery plate: 0.3 lbs (150 g)
Dimensions (W x D x H)	6-11/16" x 5-3/4" x 4-3/16" (159 mm x 146 mm x 105 mm)
Output Connectors	BS OUT (BNC x 1) GENLOCK OUT (BNC x 1) REMOTE (10 pin) INCOM (XLR x 1, 5 pin (female)) VF OUT (D-sub, 15 pin) RET OUT (BNC x 1) DC OUT (2 pin)
Input Connectors	SDI IN (BNC x 1) BS IN (BNC x 1) DC IN (5 pin) RET CTRL (6 pin) BATTERY IN (2 pin)
Accessories	REMOTE Cable, VF Cable, Battery Plate, Cable Strap, Ferrite core