



## WINDOWS 11 PRO FULLY RUGGED TABLET WITH 12" OUTDOOR FULL-HD DISPLAY

### **TOUGHBOOK 33 mk4 Tablet**

TOUGHBOOK 33 TABLET, the 12.0" fully rugged device with hot swappable twin batteries and highly configurable capabilities brings unrivalled flexibility and performance for mobile business computing. Thanks to the optional detachable keyboard, the TOUGHBOOK 33 TABLET offers the best of all worlds for mobile workers. Target industries for the device include field service workers, maintenance and service technicians in utilities and telecommunications, as well as government agencies, defence, the police and other emergency services.

#### **Key Features**

Intel Core™ i5-1345U vPro™ Processor or Intel Core™ i7 1370P vPro™ Processor

### Windows 11 Pro

12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to  $1.200 cd/m^2$ ), IP55 Digitiser

IP65 Water and dust resistant\*\*\* Tested against MILSTD810H\*\*\*

Long battery life of up to 7.5 hours with hot swap













# TOUGHBOOK 33 mk4 Tablet

### Yesterday's Legend, Today's Leader.

#### TOUGH YET VERSATILE

The Panasonic TOUGHBOOK 33mk4 is a cutting-edge, rugged tablet designed for mobile workers, featuring out-of-the-box 5G connectivity that enhances performance, reliability, and data transfer speeds in various environments. This model can connect to 5G standalone networks, catering to the increasing demand for quick, secure data transfer in the context of IoT and AI applications. It boasts improved processing power with options for the Intel® Core™ i5 or i7 processors (both 13th generation, equipped with Intel vPro® Technology).

https://eu.connect.panasonic.com/it/ en/toughbook/toughbook-33series/toughbook-33-mk4-tablet

Model	C-33mk4, 16GB RAM, 512GB SSD, 2x standard battery pack, IP55 digitiser pen
Operating System	Windows® 11 Pro
Mobile Computing Platform	Intel® Core™ i5-1345U vPro™ Processor or Intel® Core™ i7 1370P vPro™ Processor
Graphic Chip	Intel® Iris Xe Graphics (Built-in CPU)
RAM	16GB (max. 32GB) DDR4
itorage	512GB OPAL NVMe SSD (up to 2TB optional)
LCD	12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable
	glove enabled capacitive touchscreen (up to 1.200cd/m²), IP55 Digitiser
Wireless	Bluetooth: 5.3 + EDR Class 1
	Wireless LAN: Intel Wi-Fi6E AX211
	Mobile Broadband*: 4G or 5G with physical SIM and eSIM support/ 5G comes with
	extended battery
	GPS*: U-Blox NEO-M9 Series
	LAN: IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T
Interfaces	Micro SD/SDXC Memory Card: project based
	Configuration port (Tablet)**: Serial, 2D Barcode Reader, 2nd USB 2.0
	USB 3.2 Gen 1 Type A : x1
	Thunderbolt 4: x1
	USB 2.0**: x1
	HDMI: x1
	LAN Port: x1
	Headset: x1
	DC-in: x1
	Port Replicator: x1
	Dual Antenna Connector: x1
	Business Expansion Module**: Smart Card Reader, NFC, Fingerprint Reader
ront Camera	2 MP with IR / privacy shutter (Windows Hello compliant)
Rear Camera	8 mpixel with autofocus and LED flash
ound	WAVE and MIDI playback, Intel High Definition Audio subsystem support
Security	TPM (TCG V2.0 compliant) Password security (supervisor password, user password, har
	disc lock) Integrated hardware security lock slot
Pointing device: Touchscreen (Touch	Dual Touch (10 Finger touch (Capacitive) & Digitizer)
panel)	· · · · · · · · · · · · · · · ·
Dimensions: Main Unit (WxHxD)	Standard Battery: 308.0 mm × 243.6 mm × 21.6 mm / 12.1" × 9.6" × 0.9" (without
	protruding parts)
	Extended Battery: 308.0 mm x 243.6 mm x 32.1 mm / 12.1" x 9.6" x 1.3" (without
	protruding parts)
Weight: Main Unit Battery Life	Standard Battery: 1.54kg / 3.4lb
	Extended Battery: 1.9kg / 4.1lb
	Standard: Approx 7.5 hours (Mobile Mark™ 25)
	Extended: Approx 15.5 hours (Mobile Mark™ 25)
Power Supply: AC Adaptor	Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 4.06A
ower Supply: Battery	Standard: x2 Li-Ion (3 cell, 22Whr)
rower supply, battery	Extended: x2 Li-Ion (6 cell, 22 Whr) optional
tower Supply Hat Swan	
ower Supply: Hot Swap	Hot swap, Standby function, ACPI BIOS
Prop resistance	MIL-STD 810H, 150cm***
Oust resistance	IEC529 (JIS C0920) IP6x***
Vater resistance	IEC529 (JIS C0920) IPx5***
Operating temperature	MIL-STD 810H, -29 °C to 60 °C ***
ncluded in the box	Power Supply, Power Cord, Display cleaning cloth and User Manual
ootnote Description	* Optional
	** One option exclusive possible in configuration port/ business expansion module
	*** Tested by an independent third party lab following MIL-STD-810H and IEC529,
	Continue 12.4.12.6.2.14.2.5 and 14.2.5

### TOUGHBOOK 33: November 2024

Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances.

Mobile Solutions Business Division - Europe, Panasonic Connect GmbH, Hagenauer Straße 43, 65203 Wiesbaden, Germany

Sections 13.4, 13.6.2, 14.2.5 and 14.3