



**49" LCD IPS Panel, 500 cd/m², Shadowsense
Multitouch, OpenPort Platform, HTML5, narrow 6.3
mm bezel**

TH-49AF1-SST

Combines the accurate and robust ShadowSense™ Touch technology and the performance of a stand-alone solution with the Android™-based OpenPort Platform™, ideal for installations such as interactive POS and way finding signage.

Key Features

49", 500cd/m², 24/7 Operation

10-point multi-touch Interactive Display using ShadowSense™ Technology

The touch technology is immune to the ambient light and works even in bright environments.

High-performance SoC (System on a Chip) featuring a 1 GHz quad-core CPU, 1 GB of memory, and 8 GB internal storage.

Simple installation and easy operation. No need for external devices and cables.

500 cd/m²





TH-49AF1-SST

<https://eu.connect.panasonic.com/it/en/products/professional-displays/th-49af1-sst>

Screen Size	49-inch (1387 mm)
Panel Type	LCD IPS Panel/LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1123 x 653 mm
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	500 cd/m2
Contrast Ratio	1300:1
Dynamic Contrast	50000:1
Response Time	8 ms (GtoG)
Viewing Angle (Horizontal/Vertical)	178°/178°(CR≥10)
Power Requirements	110-127/220-240 V AC,50/60 Hz
Power Consumption	181W
Power Off Condition	Approx.0.3W (TBD)
Standby Condition	Approx.0.5W (TBD)
Dimensions (W x H x D)	1171 x 701 x 90mm (with handle)
Dimensions (W x H x D) Excluding Handle Part	1171 x 701 x 76mm
Bezel Width	48mm
Weight	Approx. 39,8 kg
Wall-Hanging Pitch	VESA Compliant 400 x 400 mm(15.8" x 15.8")
Operating Environment	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
Panel Surface Treatment	Anti-Glare
Haze	10%