



Display da 43 pollici con risoluzione 4K dedicato alle sale riunioni aziendali e all'uso nel mondo educational

TH-43CQE2

Il display professionale TH-43CQE2 4K è progettato per un funzionamento continuo di 16 ore al giorno e offre una qualità di visione cristallina. Il display offre una luminosità di 500 cd/m² con un pannello antiriflesso, riducendo la riflessione della luce ambiente e migliorando notevolmente la visibilità. Per una flessibilità ottimale e un aspetto pulito senza set-top-box o cavi, il TH-43CQE2 è dotato anche di un sintonizzatore TV integrato per l'accesso ai servizi TV via cavo, via etere e a pagamento, rendendoli una soluzione ideale per applicazioni aziendali, educative e anche per bar sportivi.

Key Features

Alta qualità d'immagine

Affidabilità e facilità di installazione

Scalabilità del sistema





TH-43CQE2

<https://eu.connect.panasonic.com/it/it/products/professional-displays/th-43cqe2>

Panel Panel size	43-inch class (42.51-inch/1079.8 mm)
Panel Effective display area (W x H)	941.1 x 529.4 mm (37.05" x 20.84")
Panel Resolution	3840 x 2160
Panel Brightness (typ.)	500 cd/m ²
Panel Contrast	1200:1
Panel Viewing angle [(T/B)/(L/R)]	178°/178° (CR>10)
Panel Panel surface treatment	Anti-glare (Haze 1 %)
Terminals HDMI™ IN	HDMI™ x 4 (compatible with HDCP2.2)
Terminals USB	Type A: DC 5 V/max. 0.9 A, USB 3.0 is supported, Type A: DC 5 V/max. 0.5 A, USB 2.0 is supported, Type A: DC 5 V/max. 0.5 A, USB 2.0 is supported (Internal), Type C: DC 5 V/max. 3.0 A, USB 3.0 is supported, DisplayPort Alternate mode compatible
Terminals microSD	microSD/SDHC/SDXC / MAX 1 TB
Terminals Serial In	Stereo mini jack (φ3.5 mm) x 1, RS-232C Compatible
Terminals LAN	RJ45 x 1, compatible with PLink™ 10BASE-T/100BASE-TX/1000BASE-T
Terminals IR In	Stereo mini jack (φ3.5 mm) x 1
Terminals Slot	No
Terminals Wi-Fi	Yes (Built-in)
Terminals Bluetooth®	Yes (Built-in)
Terminals Audio Out	Stereo mini jack (φ3.5 mm) x 1, SPDIF x 1
HTML browser	HTML5 (Vwed)
Android™-OS	Yes
Operating time*1	16 h/day
Orientation	Landscape/Portrait
Tilt angle*2	0-20 degrees forward with landscape setting
Built-in Speaker	16 W
Power Supply	AC 220-240 V50 Hz/60 Hz, 0.9 A
Power Consumption	110 W (Shipping Condition)
On Mode Average Power Consumption*3	110 W (Picture Mode: [Natural])
Power Off Condition	Approx. 0 W
Stand-by Conditions	Approx. 0.5 W
Energy efficiency class	G
Dimension (WxHxD) (Excluding remote IR sensor)	964 x 555 x 68 mm(37.92" x 21.85" x 2.66")
Peso	10.3 kg/22.7 lbs
Bezel Width	11 mm (0.43") (T/R/L), 13.8 mm (0.54") (B)
Wall-Hanging Pitch	200 x 200 mm, M6
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

Note
*1: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images. *2: Please contact your sales representative with regard to the tilt angle before installation. *3: Based on IEC 62087 Ed.2 measurement method.