

Dotato di funzionalità avanzate di alto livello, è una soluzione sottile, leggera e scalabile che agevola qualsiasi installazione. Pannello Ultra HD 4K da 55", Intel® SDM (Smart Display Module), funzionamento 24/7, installazione verticale, Digital Link 4K, cornice sottile

TH-55SQ1

Display 4K per digital signage professionale ed elegante. Dotato di funzionalità avanzate di alto livello, è una soluzione sottile, leggera e scalabile che agevola qualsiasi installazione. Pannello Ultra HD 4K da 55", Intel® SDM (Smart Display Module), funzionamento 24/7, installazione verticale, Digital Link 4K, cornice sottile

Key Features


Pannello IPS 4K da 55", 500 cd/m2, con design sottile ed elegante e funzionamento 24/7

Elevata qualità dell'immagine grazie alla tecnologia HDR (sistema HLG) che riproduce immagini chiare e scure in modo realistico

Letto multimediale USB 4K: elimina la necessità di dispositivi esterni e consente gli aggiornamenti tramite rete LAN

Altamente espandibile, con Intel® SDM (Smart Display Module) ultrasottile, connessione DisplayPort per digital signage in Daisy-Chain, funzione multischermo (modalità quadrupla, PinP, PbyP) e DIGITAL LINK 4K

Installazione flessibile e leggera, in verticale o in orizzontale



TH-55SQ1

<https://eu.connect.panasonic.com/it/it/products/professional-displays/th-55sq1>

Screen size (diagonal) (inch)	55-inch (1387.8 mm)
Screen size (diagonal) (mm)	1387.8 mm
Aspect Ratio	16:9
Panel Type	IPS Panel / Edge-LED
Effective display area (W x H) (mm)	1209.6 x 680.4 mm
Effective display area (W x H) (inch)	47.62 x 26.78 inch
Risoluzione	3840 x 2160
Brightness (typ.)	500 cd/m ²
Contrast Ratio	1100:1 (Typ)
Response Time	8 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178°/178° (CR _{≥10})
Panel Surface Treatment	Anti-Grare Type (Haze 28%)
Terminals HDMI In	HDMI TYPE-A Connector x 2
Terminals DisplayPort IN	DisplayPort x 1
Terminals DisplayPort OUT	DisplayPort x 1
Terminals DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with PC In)
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)
Terminals Serial	D-sub 9-pin x 1, RS232C Compatible
Terminals IR IN / OUT	Stereo Mini Jack (M3) x 1 / x 1
Terminals Audio Out	30 W [15 W + 15 W] 10% THD
Terminal LAN	RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™
Terminal DIGITAL LINK	RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™
Terminals Slot	Intel® SDM specification
Terminals USB	Corresponding size SDM-S / SDM-L USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	110–240 V AC, 50 Hz/60 Hz
Power Consumption	300W
Power Off Condition	Approx. 0.3 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1240 x 714 x 74 mm *Including handles
Dimensions (W x H x D) (inch)	48.9" x 28.1" x 2.9" *Including handles
Weight (kg)	Approx. 25.5 kg
Weight (lbs.)	Approx. 56.3 lbs.
Bezel width (mm)	12.2 mm(T), 15.8 mm (B), 12.7 mm (L/R)
Bezel width (inch)	0.48" (T), 0.62" (B), 0.50" (L/R)
Wall-hanging pitch (mm)	400 x 400 mm VESA Compliant
Wall-hanging pitch (inch)	15.8" x 15.8" VESA Compliant
Orientation	Landscape/Portrait
Tilting angle	Landscape setting: 0 - 45 degrees forward/backward Portrait setting: 0 - 45 degrees forward/backward
Operating Time	24 h/day
Operating environment Temperature	Temperature : 0 °C to 40 °C / Humidity: 20% to 80% (Non-condensation)