



Unità di controllo telecamera

AW-RP50 Controllo versatile della telecamera con semplici operazioni

Controller remoto compatto e intuitivo

Key Features

Utilizzando una connessione seriale è possibile controllare fino a 5 teste da microcamera/Pan-Tilt

Controllo multiplo: Fino a 5 AW-RP50 possono controllare simultaneamente una singola unità telecamera remota

Fino a 100 memorie preimpostate sono disponibili per ogni telecamera

Fino a 100 unità telecamera remota si possono controllare tramite hub IP ed Ethernet

Da un singolo PC si possono configurare varie impostazioni (software di configurazione fornito)



AW-RP50 Controllo
versatile della
telecamera con
semplici operazioni

<https://eu.connect.panasonic.com/it/it/products/broadcast-proav/aw-rp50-controllo-versatile-della-telecamera-con-semplici-operazioni>

Power Supply	DC 12 V ±10 % (AC adapter provided)
Power Consumption	0.5 A (With DC1 2V)
Peso	Approx. 1.1 kg (Approx.2.4 lbs)
Dimensioni (LxAxP)	210 mm x 67 mm x 177 mm (8-1/4 inches x 2-9/16 inches x 6-15/16 inches) (excluding protrusions)
Accessory	AC Adaptor, Power cable
Protocol	IPv4, RS-422 (Panasonic AW series protocol)
LAN	10BASE-T/100BASE-TX (for IP control)/RJ45 x 1
Temperatura di funzionamento	0 °C to 40 °C
Operating Humidity	10 % to 90 % (no condensation)
Collegamento	IP : 1
Adjustment Functions	Pan/Tilt, Zoom, Focus, Iris, Gain, Pedestal, Shutter, Detail, White Balance (Auto, R/B Gain), Black Balance (Auto, R/B Pedestal), Switch scene files
Preset Memory	Up to 100 sets
Switcher Supported	AW-HS50
Linkage	Camera information display, Tally information imported, Bus material selection (AUX/PWW/PinP/KEY-F), Parameter Changes (Pan/Tilt lever, Zoom button)
T0 Pan/Tilt Head	RS-422 (for Serial control)/RJ45 x 5
Tally/GPI	TALLY INPUT x 5 channels GPI INPUT x 4 channels GPI OUTPUT x 4 channels/D-sub 15 pin (female) x 1