



Écran professionnel 4K de 50 pouces idéal pour les applications professionnelles et éducatives

TH-50EQ2

Écran professionnel 4K de 50 pouces idéal pour les applications professionnelles et éducatives

Key Features

Périphériques faciles à connecter (appareil photo / haut-parleur) directement à l'écran

Augmentation du type d'entrée et du nombre d'entrées disponibles

Emplacement de fonction pour des fonctionnalités accrues

Une visibilité plus élevée en raison de la luminosité que l'on trouve généralement sur les produits haut de gamme

Flexibilité d'installation – portrait et inclinaison pris en charge





TH-50EQ2

<https://eu.connect.panasonic.com/lu/fr/products/professional-displays/th-50eq2>

Screen size (diagonal) (inch)	49.5-inch (1257.3 mm)
Screen size (diagonal) (mm)	49.5-inch (1257.3 mm)
Aspect Ratio	16:9
Effective display area (W x H) (mm)	1095.8 x 616.4 mm (43.14" x 24.26")
Effective display area (W x H) (inch)	1095.8 x 616.4 mm (43.14" x 24.26")
Résolution	3840 x 2160
Brightness (typ.)	500 cd/m2
Contrast Ratio	5000:1
Response Time	9.5 ms
Viewing angle [(T/B)/(L/R)]	178°/178° (CR>10)
Panel Surface Treatment	Anti-glare type (Haze 25%)
Terminals HDMI In	TYPE A Connector x 3 (HDCP2.2 supported)
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1
Terminals Serial	D-sub 9-pin x 1, RS232C Compatible
Terminals Audio Out	Stereo Mini Jack (M3) x 1
Terminals LAN	RJ45 x 1, RJ45 10BASE-T/100BASE-TX
Terminals USB	Type A: DC 5 V/1 A, USB 3.0 is supported, Type A: DC 5 V/2 A, USB 2.0 is supported, Type C: max ~ 60W (Power Delivery compatible), USB2.0 is supported, DisplayPort Alternate mode compatible
Terminals Slot	SDM-S / SDM-L, 3.3 V/max.1.1 A, 12 V/max 5.5 A
Built-in Speaker	20W [10 W + 10 W]
Power Requirements	AC 110 - 240 V 50 Hz / 60 Hz
Power Consumption	255 W
Power Off Condition	Approx. 0.3 W
Standby Condition	Approx. 0.5 W
Weight (kg)	15.5 kg (34.2 lbs.)
Weight (lbs.)	15.5 kg (34.2 lbs.)
Bezel width (mm)	14.9 mm (0.59") (T/R/L/B)
Bezel width (inch)	14.9 mm (0.59") (T/R/L/B)
Wall-hanging pitch (mm)	VESA Compliant 400 x 400 mm (15.8" x 15.8"), M6
Wall-hanging pitch (inch)	VESA Compliant 400 x 400 mm (15.8" x 15.8"), M6
Orientation	Landscape/Portrait
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400-2800 m (4593 ft to 9186 ft)
Tilting angle*2	0 - 20 degrees forward/backward with landscape/portrait setting
Operating time*3	18 h/day
Note	1: Including handles. 2: Please contact your sales representative with regard to the tilt angle before installation. 3: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.
Dimensions (W x H x D*1)	1129 x 649 x 66 mm (44.43" x 25.56" x 2.60")