



**1DLP - 7000 lumens - WXGA - 2Lamps - RBG Booster,
Digital Link**

PT-DW750

The quietest high brightness fixed installation projector Designed for
for museums, exhibitions and digital signage applications

Key Features

1-Chip DLP, 7000 lumens, WXGA

Dual lamp system with up to 6000 hours lamp life (in eco mode). Lamp relay mode enables 24/7 operation

Dust-resistant optical engine allows filter-less design

Multi-screen support including edge blending and colour matching function



PT-DW750

<https://eu.connect.panasonic.com/nl/en/products/projectors/pt-dw750>

Power Supply	100-240 V AC, 9.0-4.0 A, 50/60 Hz
Power Consumption	790 W (810 VA) (0.3 W with STANDBY MODE set to ECO, 3 W with STANDBY MODE set to NORMAL)
	max. 2,696 BTU (without light output: 2,601 BTU)
DLP™ Chip Panel Size	mm (0.65 in) diagonal (16:10 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ system
DLP™ Chip Pixels	1,024,000 (1,280 x 800) x 1, total of 1,024,000 pixels
Lens	PT-DW750W/DW750B Powered zoom/focus lenses (1.7-2.4:1), F 1.7-1.9, f 25.6-35.7 mm PT-DW750LW/DW750LB Optional powered zoom/focus lenses and fixed-focus lens
Lamp	310 W UHM lamps (x 2)
Screen Size	1.27-15.24 m (50- 600 inches) *1.27 - 5.08 m (50 - 200 inches) with the ET-DLE055 (16:10 aspect ratio) *2.54 - 8.89 m (100 - 350 inches) with the ET-DLE030 (16:10 aspect ratio)
Brightness	7,000 lumens (dual lamp, LAMP MODE: NORMAL)
Center-to-Corner Uniformity	90%
Contrast	3,000:1 (full on/full off, in dynamic iris 3 mode)
Resolution	1,280 x 800 pixels
Scanning Frequency HDMI/DVI-D	fH: 15-100 kHz, fV: 24-120 Hz, dot clock: 25-162 MHz
Scanning Frequency RGB	fH: 15-100 kHz, fV: 24-120 Hz, dot clock: 20-162 MHz
Scanning Frequency YPBPR (YCBCR)	525i (480i): fH 15.75 kHz; fV 60 Hz, 625i (576i): fH 15.63 kHz; fV 50 Hz, 525p (480p): fH 31.50 kHz; fV 60 Hz, 625p (576p): fH 31.25 kHz; fV 50 Hz, 750 (720)/60p: fH 45.00 kHz; fV 60 Hz, 750 (720)/50p: fH 37.50 kHz; fV 50 Hz, 1125 (1035)/60i: fH 33.75 kHz; fV 60 Hz, 1125 (1080)/60i: fH 33.75 kHz; fV 60 Hz, 1125 (1080)/50i: fH 28.13 kHz; fV 50 Hz, 1125 (1080)/25p: fH 28.13 kHz; fV 25 Hz, 1125 (1080)/24p: fH 27.00 kHz; fV 24 Hz, 1125 (1080)/24sF: fH 27.00 kHz; fV 48 Hz, 1125 (1080)/30p: fH 33.75 kHz; fV 30 Hz, 1125 (1080)/60p: fH 67.50 kHz; fV 60 Hz, 1125 (1080)/50p: fH 56.25 kHz; fV 50 Hz
Scanning Frequency Video/S-Video	fH: 15.75 kHz, fV: 60 Hz [NTSC/NTSC4.43/PAL-M/PAL60] fH: 15.63 kHz, fV: 50 Hz [PAL/PAL-N/SECAM]
Optical Axis Shift	Vertical: -16% - +60% (powered), horizontal: -10% - +30% (powered) (-10% - +28% with the ET-DLE085/DLE105) NOTE: Optical axis shift function cannot be operated when used with the ET-DLE055. If using the ET-DLE030, the optical axis is fixed.
Keystone Correction Range	Vertical ±40°, horizontal: ±15° (Vertical: ±22° with the ET-DLE055/DLE085/DLE105), (Vertical: ±5° with the ET-DLE030) Curved correction (Geometric adjustment) 4 corner correction
Installation	Ceiling/floor, front/rear
Terminals HDMI In	HDMI 19-pin x 1, Deep Color, compatible with HDCP
Terminals DVI-D In	DVI-D 24-pin x 1, DVI 1.0 compliant, HDCP compatible, for single link only
Terminals RGB 1 In	BNC x 5

Terminals RGB 1 In R, G, B	R: 0.7 Vp-p, 75 ohms, G: 0.7 Vp-p (G: 1.0 Vp-p for sync on G), 75 ohms, B: 0.7 Vp-p, 75 ohms HD, VD/SYNC: TTL, high impedance, positive/negative automatic NOTE: SYNC/HD and VD terminals do not accept tri-level sync signals.
Terminals RGB 1 In Y, PB, PR (Y, CB, CR)	Y: 1.0 Vp-p (including sync signal), PB/PR (CB/CR): 0.7 Vp-p, 75 ohms
Terminals RGB 1 In S-Video Signal	Y: 1.0 Vp-p, C: 0.286 Vp-p, 75 ohms
Terminals RGB 1 In Video Signal	1.0 Vp-p, 75 ohms
Terminals RGB 2 In	D-sub HD 15-pin (female) x 1
Terminals RGB 2 In R, G, B	R: 0.7 Vp-p, 75 ohms, G: 0.7 Vp-p (G: 1.0 Vp-p for sync on G), 75 ohms, B: 0.7 Vp-p, 75 ohms HD, VD/SYNC: TTL, high impedance, positive/negative automatic NOTE: SYNC/HD and VD terminals do not accept tri-level sync signals.
Terminals RGB 2 In Y, PB, PR (Y, CB, CR)	Y: 1.0 Vp-p (including sync signal), PB/PR (CB/CR): 0.7 Vp-p, 75 ohms
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals Serial Out	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Terminals Remoter 1 In	M3 jack x 1 for wired remote control
Terminals Remoter 1 Out	M3 jack x 1 for link control
Terminals Remoter 2 In	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals LAN/DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK (video/network/serial control) connection, 100Base-TX, compatible with Art-Net, compliant with PjLink™ (class 1), Deep Color, compatible with HDCP,
Terminals USB	DC OUT (5V/0.9A)
Power Cord Length	3.0 m (9 ft 10 in)
Cabinet Materials	Molded plastic (PT-DW750W/DW750LW : White) (PT-DW750B/DW750LB : Black)
Dimensions (W x H x D)	498 x 175 x 521 mm (19-19/32 x 6-7/8 x 20-1/2 inches) (with supplied lens) 498 x 175 x 508 mm (19-19/32 x 6-7/8 x 20 inches) (without lens, with lens cover) 498 x 175 x 498 mm (19-19/32 x 6-7/8 x 19-19/32 inches) (without lens and lens cover)
Weight	Approx. 17.8 kg (39.2 lbs) (with supplied lens) Approx. 17.0 kg (37.5 lbs) (without lens)
Operating Noise	30 dB (dual lamp operation, LAMP MODE: NORMAL), 28 dB (dual lamp operation, LAMP MODE: ECO)
Operating Temperature	0-45 °C (32-113 °F)
Operating Humidity	10%-80% (no condensation)
Technology	1-Chip DLP
Note	Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. *1 When the STANDBY MODE is set to ECO, network functions such as power on over the LAN network will not operate, and the serial output terminal cannot be used. Also, only certain commands can be received for external control using the serial terminal. *2 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *3 With legs at shortest position. *4 Average value. May differ depending on models. *5 The operating temperature range is 0 °C to 40 °C (32 °F to 104 °F) when the fan control is set to High Altitude mode (for altitudes from 1,400 m to 2,700 m (4,593 ft to 8,858 ft) above sea level). Also, if the ambient temperature exceeds 40 °C (104 °F) (35 °C (95 °F) in High Altitude mode) when the projector is being used with Lamp Select set to Dual and Lamp Power set to High, the light output may be reduced approximately 20% to protect the projector.