



98-inch klasse 4K-instapmodel dat flexibel past bij zakelijke vergaderruimten en educatief gebruik.

TH-98CQE2

Het Panasonic Connect TH-98CQE2 4K Professional-scherm is ontworpen voor 24 uur per dag continu gebruik en kristalheldere kijkhelderheid. Het scherm biedt een helderheid van 500cd/m² met een antireflectiepaneel en een minimale nevelbehandeling, waardoor de reflectie van omgevingslicht wordt verminderd en de zichtbaarheid aanzienlijk wordt verbeterd. Voor ultieme flexibiliteit en een strakke look zonder settopboxen of kabels, is de TH-98CQE2 ook uitgerust met een ingebouwde tv-tuner voor toegang tot broadcast-, kabel- en abonnements-tv-diensten, waardoor ze een ideale oplossing zijn voor zakelijke, educatieve en zelfs sportbartoepassingen.

Key Features

Hoge beeldkwaliteit

Betrouwbaarheid en installatiegemak

Schaalbaarheid van het systeem





TH-98CQE2

<https://eu.connect.panasonic.com/nl/nl/products/professional-displays/th-98cqe2>

Panel Panel size	98-inch class (97.51-inch/2476.9 mm)
Panel Effective display area (W x H)	2158.8 x 1214.3 mm (84.99" x 47.80")
Panel Resolution	3840 x 2160
Panel Brightness (typ.)	500 cd/m2
Panel Contrast	1200:1
Panel Viewing angle [(T/B)/(L/R)]	178°/178° (CR>10)
Panel Panel surface treatment	Anti-glare (Haze 25 %)
Terminals HDMI™ IN	HDMI™ x 4 (compatible with HDCP2.2)
Terminals USB	Type A: DC 5 V/max. 0.9 A, USB 3.0 is supported, Type A: DC 5 V/max. 0.5 A, USB 2.0 is supported (Internal), Type C: DC 5 V/max. 3.0 A, USB 3.0 is supported, DisplayPort Alternate mode compatible
Terminals microSD	microSD/SDHC/SDXC / MAX 1 TB
Terminals Serial In	Stereo mini jack (φ3.5 mm) x 1, RS-232C Compatible
Terminals LAN	RJ45 x 1, compatible with PLink™ 10BASE-T/100BASE-TX/1000BASE-T
Terminals IR In	Stereo mini jack (φ3.5 mm) x 1
Terminals Slot	No
Terminals Wi-Fi	Yes (Dongle)
Terminals Bluetooth®	Yes (Dongle)
Terminals Audio Out	Stereo mini jack (φ3.5 mm) x 1, SPDIF x 1
HTML browser	HTML5 (Vwed)
Android™-OS	Yes
Operating time*1	24 h/day
Orientation	Landscape/Portrait
Tilt angle*2	0-20 degrees forward and backward with landscape/ portrait setting
Built-in Speaker	24 W
Power Supply	AC 220-240 V 50 Hz/60 Hz, 3.3 A
Power Consumption	445 W (Shipping Condition)
On Mode Average Power Consumption*3	410 W (Picture Mode: [Natural])
Power Off Condition	Approx. 0 W
Stand-by Conditions	Approx. 0.5 W
Energy efficiency class	-
Dimension (WxHxD) (Excluding remote IR sensor)	2216 x 1271 x 91 mm(87.25" x 50.02" x 3.55")
Weight	99.4kg/219.2 lbs
Bezel Width	28.2 mm (1.11") (T/R/L/B)
Wall-Hanging Pitch	800 x 400 mm, M8
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)
Note	*1: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images. *2: Please contact your sales representative with regard to the tilt angle before installation. *3: Based on IEC 62087 Ed.2 measurement method.