



Remote Operation Panel (ROP)

AK-HRP1000

1/4-type rack size remote operation panel which supports PoE+ and IP control

Key Features

1/4-type rack size remote operation panel

Colour LCD readout display allows GUI operation, and also supports PoE+ and IP control

Variable master gain, colour temperature and master flare can all be assigned to a user knob

Joystick control lever allows Iris/Pedestal operation

Can be used with a mix of studio and Panasonic remote control cameras via IP connection



AK-HRP1000

<https://eu.connect.panasonic.com/n/en/products/broadcast-proav/ak-hrp1000>

Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC)
	42 V - 57 V DC (PoE power supply)
Power Consumption	0.51 A (Power supply from camera: 10 V - 16 V DC)
	0.15 A (PoE power supply)
Operating Temperature	0°C to 40°C (32°F to 104°F)
Humidity	90% or less
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Weight	Approx. 1.7 kg (3.75 lb)
Dimensions (W x H x D)	102 mm x 385 mm x 113 mm
	(4 inches x 15-3/16 inches x 4-7/16 inches)
Camera/CCU Control	Control signals (camera, CCU control)
	Power supply 16 V DC (when CCU connected)*4,
	12 V DC (when camera connected)*4
Maximum Cable Length	When camera connected: 20 m (65.7 ft)
	When CCU connected: 50 m (164 ft)
Compatibility	-
Note	*1: Depending on the setting, only one of them can be selected at one time.
	*2: The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically.
	*3: IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF].
	*4: Can be provided from CCU