



**Thin and stylish design with narrow bezel and supports LAN and RS232C control, ideal for corporate. 65", 400 cd/m<sup>2</sup>, stylish design display with narrow bezel and VA/LED panel for clear off-axis visibility**

## TH-65CQ1

Thin and stylish design with narrow bezel, offering meeting room application with easy installation and high connectivity, ideal for corporate installations

### Key Features

---

65", 400 cd/m<sup>2</sup>

---

4K UHD LCD display delivers highly detailed content with contrast adjustments that enhance image quality

---

VA/LED Panel for superb viewing experience from any angle

---

Sleek and stylish design with narrow bezel and easy installation with built-in speakers and basic terminals

---

Easy and versatile control options using HDMI® CEC or RS-232C/LAN control for efficient operation





## TH-65CQ1

<https://eu.connect.panasonic.com/en/products/professional-displays/th-65cq1>

<b>Screen size (diagonal) (inch)</b>	64.5-inch
<b>Screen size (diagonal) (mm)</b>	1638 mm
<b>Aspect Ratio</b>	16:9
<b>Panel Type</b>	VA / Direct-LED
<b>Effective display area (W x H) (mm)</b>	1428 x 803 mm
<b>Effective display area (W x H) (inch)</b>	56.2" x 31.6"
<b>Resolution</b>	3840 x 2160
<b>Brightness (typ.)</b>	400 cd/m2
<b>Contrast Ratio</b>	5000 : 1
<b>Response Time</b>	8 ms (G to G)
<b>Viewing angle [(T/B)/(L/R)]</b>	178° / 178° (CR≥20)
<b>Terminals   HDMI In</b>	HDMI TYPE-A Connector x 2
<b>Terminals   PC IN/AUDIO IN (L/R)</b>	Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1
<b>Terminals   Serial</b>	D-sub 9-pin x 1 (Input, RS-232C Compatible)
<b>Terminals   Audio Out</b>	Pin Jack x 1
<b>Terminals   LAN</b>	RJ45 x 1, 10 BASE-T / 100 BASE-TX
<b>Terminals   USB</b>	USB Connector (TYPE-A) x 1, DC 5V/0.5A (USB 2.0 Supported)
<b>Built-in Speaker</b>	20 W [10 W + 10 W]
<b>Power Requirements</b>	AC 110 - 127 V 50 Hz / 60 Hz
<b>Power Consumption</b>	136w
<b>Power Off Condition</b>	Approx. 0.5 W
<b>Standby Condition</b>	Approx. 0.5 W
<b>Dimensions (W x H x D) (mm)</b>	1463 x 847 x 97 mm
<b>Dimensions (W x H x D) (inch)</b>	57.6" x 33.4" x 3.8"
<b>Bezel width (mm)</b>	T/R/L 15.9 mm B 19.9 mm
<b>Bezel width (inch)</b>	T/R/L 0.63" B 0.78"
<b>Weight (kg)</b>	Approx.33 kg
<b>Weight (lbs.)</b>	Approx. 72.8 lbs
<b>Wall-hanging pitch (mm)</b>	400 x 200 mm VESA compliant
<b>Wall-hanging pitch (inch)</b>	VESA Compliant 15.7" x 7.9" (400 x 200 mm) (Installed by: M6 screws / Screw hole depth 0.7" (17 mm))
<b>Operating Time</b>	16 h/day
<b>Operating Environment</b>	Temperature : 32°F to 104°F (0°C to 40°C)*1 : 32°F to 95°F (0°C to 35°C)*2 Humidity : 20% to 80% (No condensation)