



A contactless and secure delivery and returns solution available in 4 different temperature options.

Smartlocker

A modular, scalable design with four temperature options, Smartlocker is a rapid, secure and contactless delivery solution that allows goods to be ordered, collected and returned by your customers easily, efficiently and most importantly...flexibly.

Key Features

4 temperature options

Cloud model

Monitor camera

LED Indicator (lock status)

Door handle

Barcode scanner

Monitor camera

Smartlocker

<https://eu.connect.panasonic.com/tr/en/products/supply-chain-management/smartlocker>

Size	Chiller / Freezer / Heated Unit (per 1 Unit): Height: 248.5 cm Length: 120 cm Width top: 153.9 cm Width bottom: 88.7 cm
Cloud Model	<ul style="list-style-type: none"> - Easy integration with ecommerce platform - Seamless upgrade to cloud-based version - No hardware change needed - Remote monitoring and troubleshooting - Customisable UI/UX design - LAN/Wi-Fi 3G/4G (connection) - Back-office locker management - Cloud agnostic architecture - Data encryption for security - Temperature monitoring and alarming - Built-in self-diagnostics tool
Payment Model	CAPEX, SaaS, and OPEX leasing options available
Temperature Options	Heated Ambient Chilled Freezer
Additional equipment	CCTV camera UPS 3G/4G Router
Optional Service	Connect to cloud backend system SMS service Integration to customer app
Different variations	6, 8, 10, 12 Door Unit & Controller Unit
Operating Temperature	INDOOR USE : 5 ~ 40°C OUTDOOR USE: -20 ~ 40°C
Network Interface	RJ45
Noise Level	Lower than 55dB
Weight (kg)	Controller: 150 kg Ambient: 220 kg Chiller: 260 kg Freezer / Heated: 280 kg
Power Supply	AC220-240V, 50Hz
Screen	Indoor: 21.5 inch touch screen. Vertical installation Outdoor: 21.5 inch Waterproof high brightness and anti-glare touch screen, Vertical installation
Color	Indoor: SN-07(White) / Other color is available as option Outdoor: N-07(White) / Other color is available as option Whether resistance coating
Chamber size per door	6 door: 337x465x443 / 410 L 8 door: 337x465x318 / 394 L 10 door: 337x465x243 / 380 L 12 door: 337x465x192 / 370 L

Air temperature inside Chamber	Indoor: Chiller Type 1:1 ~ 4°C Chiller Type 2:12~18°C Freezer SKU: -15 ~ -18°C Heater SKU: 60~70°C Ambient SKU: same temperature as ambient
	Outdoor: Ambient SKU: same temperature as ambient Chiller Type 1: 1 ~ 7°C (with heater) Chiller Type 2: 12~18°C (with heater) Freezer SKU: 15 ~ -18°C
Refrigerant	R290
Cooling Mode	Air Cooling
Defrost	Chiller SKU Type 1 & 2: Nature defrost
	Freezer SKU: Electric heating defrosting. Digital controller periodic defrosting
Drain	Indoor: Chiller SKU Type 1 & 2: Direct drain or Optional Forced Evaporation Tray Freezer SKU: Direct drain or Optional Forced Evaporation Tray
	Outdoor: Chiller SKU Type 1 & 2: Direct drain Freezer SKU: Direct drain
Door type	Indoor: Ambient SKU: Foaming door Chiller SKU Type 1 & 2: Foaming Door Freezer SKU: Foaming Door Heater SKU: Glass Door
	Outdoor: Ambient SKU: Foaming door Chiller SKU Type 1 & 2: VIP insulation door Freezer SKU: VIP insulation door
LED indicator on doors	yes
Dast and whether resistance	Indoor: IP2X(No waterproof for the whole product)
	Outdoor: IP25 (Optional framework is necessary)
Barcode scanner	yes
Bearing capacity of the shelving inside the chamber	50 kg
Chamber type	Chiller, Freezer, Ambient: 6 / 8 / 10 / 12 door
	Heated:6 / 8 / 10 door
1SKU Size (WxDxH mm)	Indoor: 1200x700x2200
	Outdoor: 550x640x2050 (w/o frame)
Frame	Indoor: not required
	Outdoor: Required
Size Control Unit	Height: 248.5 cm
	Length: 54.6 cm
	Width top: 153.9 cm
	Width bottom: 88.7 cm