



Zaprojektowany z myślą o wysokiej jasności w audytoriach i salach konferencyjnych. Projektor LCD o jasności 5300 lumenów i rozdzielczości XGA.

PT-EX520

Kompaktowy i wszechstronny projektor LCD Zaprojektowany z myślą o wysokiej jasności w audytoriach i salach konferencyjnych

Key Features

Technologia LCD, jasność 5300 lumenów, rozdzielczość XGA

Wysoka jasność w kompaktowej i lekkiej konstrukcji

Odporna na pył obudowa i filtr ekologiczny zapewniający nawet 15 000 godzin pracy bez konserwacji

Przemieszczanie obiektywu za pomocą silnika i szeroka gama opcjonalnych obiektywów





PT-EX520

<https://eu.connect.panasonic.com/pl/pl/products/projectors/pt-ex520>

Power Supply	AC100 - 240V 5.3 - 2.1A 50Hz/60Hz
Power Consumption	461 W
Power Consumption Standby Mode (Eco)	0.5W, 0.3W (Taiwan)
Power Consumption Standby Mode (Normal)	8W
Power Consumption Standby Mode (Normal and Audio Monitor Out)	22W
BTU Value	Max 1,573 BTU
LCD Panel Panel Size	16.0 mm (0.63 in) diagonal (4:3 aspect ratio)
LCD Panel Display Method	Transparent LCD panel (x 3, R/G/B)
LCD Panel Drive Method	Active matrix
LCD Panel Pixels	786,432 (1,024 x 768) x 3, total of 2,359,296 pixels
Lens	Powered zoom (throw ratio 1.32-2.44:1), powered focus, F 1.6-2.2, f 17.1-31.7 mm
Lamp	320 W UHM lamp Lamp replacement cycle 4,000 hours (lamp power: Normal), 5,000 hours (lamp power: Eco) This is the maximum value when the lamp is turned on for 2 hours and off for 0.25 hours.
Screen Size	1.02- 10.16 m (40-400 inches) (4:3 aspect ratio)
Brightness	5,300 lumens (Lamp power: Normal, Dynamic mode, Daylight View:off, Auto Power Save:off)
Center-to-Corner Uniformity	90%
Contrast	2,000:1 (Lamp power: Normal, Dynamic mode, Daylight View:off, Auto Power Save:off)
Resolution	1,024 x 768 pixels
Scanning Frequency HDMI	fH: 15- 90kHz, fV: 24 - 100Hz, dot clock: 25 - 162 MHz
Scanning Frequency RGB	fH: 15- 90kHz, fV: 24 - 100Hz, dot clock: 162 MHz or lower
Scanning Frequency YPBPR (YCBCR)	525i (480i): fH15.73 kHz; fV59.94 Hz, 625i (576i): fH15.63 kHz; fV50 Hz, 525p (480p): fH31.47 kHz; fV60 Hz, 625p (576p): fH31.25 kHz; fV50 Hz, 750 (720)/60p: fH45.00 kHz; fV60 Hz, 750 (720)/50p: fH37.50 kHz; fV50 Hz, 1125 (1080)/60i: fH33.75 kHz; fV60 Hz, 1125 (1080)/50i: fH28.13 kHz; fV50 Hz, 1125 (1080)/25p: fH28.13 kHz; fV25 Hz, 1125 (1080)/24p: fH27.00 kHz; fV24 Hz, 1125 (1080)/24sF: fH27.00 kHz; fV48 Hz, 1125 (1080)/30p: fH33.75 kHz; fV30 Hz, 1125 (1080)/60p: fH67.50 kHz; fV60 Hz, 1125 (1080)/50p: fH56.25 kHz; fV50 Hz
Scanning Frequency Video/S-Video	fH: 15.75 kHz, fV: 59.94 Hz [NTSC/NTSC4.43/PAL-M/PAL60] fH: 15.63 kHz, fV: 50 Hz [PAL/PAL-N/SECAM]
Keystone Correction Range	Vertical $\pm 25^\circ$, horizontal $\pm 30^\circ$
Optical Axis Shift	Vertical: $\pm 50\%$ (powered) Horizontal: $\pm 30\%$ (powered)
Installation	Ceiling/floor, front/rear
Speaker	4.0 cm (1.9/1.6 in) (monaural) x 1
Terminals HDMI In 1/HDMI In 2 HDMI 19-Pin x2	Deep Color, compatible with HDCP, Audio signal: linear PCM (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
Terminals RGB 1 In	BNC x 5
Terminals RGB 1 In R, G, B	0.7 Vp-p, 75 ohms, (G: 1.0 Vp-p, 75 ohms for sync on G) HD/VD, SYNC: TTL, high impedance, positive/negative automatic

Terminals RGB 1 In Y, PB, PR (Y, CB, CR)	Y : 1.0 Vp-p (including sync signal), PBPR(CBCR): 0.7 Vp-p,75 ohms
Terminals RGB 1 In Y/C	Y: 1.0 Vp-p(including sync signal), C: 0.286 Vp-p,75 ohms
Terminals RGB 2 In	D-sub HD 15pin(female) x 1
Terminals RGB 2 In R, G, B	0.7 Vp-p, 75 ohms, (G: 1.0 Vp-p,75 ohms for sync on G) HD/VD, SYNC: TTL, high impedance, positive/negative automatic NOTE: SYNC/HD and VD terminals do not accept tri-level sync signals.
Terminals RGB 2 In Y, PB, PR (Y, CB, CR)	Y : 1.0 Vp-p (including sync signal), PBPR(CBCR): 0.7 Vp-p, 75 ohms
Terminals Video In	Pin jack x 1, 1.0 Vp-p, 75 ohms
Terminals Monitor Out	D-sub HD 15pin(female) x 1
Terminals Monitor Out R, G, B	0.7 Vp-p, 75 ohms, (G: 1.0 Vp-p, 75 ohms for sync on G) HD/VD, SYNC: TTL, high impedance, positive/negative automatic
Terminals Monitor Out Y, PB, PR	Y: 1.0 Vp-p (including sync signal), PBPR: 0.7 Vp-p, 75 ohms
Terminals Audio In 1/Audio In 2	M3 x 2, 0.5 Vrms, input impedance: 22 kilohms or more
Terminals Audio In 3	Pin jack(L, R) x 1, 0.5 Vrms, input impedance: 22 kilohms or more
Terminals Variable Audio Out	M3 x 1 (monitor out, stereo) 0-2.0 Vrms, variable, output impedance: 2.2 kilohms or less
Terminals Serial In	D-sub 9 p x 1, for external control (RS232C compliant)
Terminals Remoter 1 In	D-sub 9-pin (female) x1, for external control (parallel)
Terminals Remoter 2 In	M3 jack x 1 for wired remote control
Terminals LAN	RJ45 x 1 for network connection 10Base-T/100Base-TX, compatible with Art-Net,PJLink™(Class 1)
Terminals Wireless	USB Type A x 1, for wireless projection with optional dongle (ET-WML100)
Terminals DC Out	USB Type A x 1, for power supply (DC5 V, max 900 mA)
Power Cord Length	3.0 m (9 ft10 in)
Cabinet Materials	Molded plastic
Dimensions (W x H x D)	498 x 145 x 398.3mm (19-19/32 x 5-11/16 x 15-11/16 in) with supplied lens
Weight	Approx. 8.4kg (18.5lbs)
Operating Noise	29 dB (Silent), 35 dB (Normal/Eco)
Operating Environment Operating Temperature	0-45 °C (32-113 °F)
Operating Environment Operating Humidity	20%-80%
Technology	LCD